

# PRESSURE & TEMPERATURE INSTRUMENT QUICK GUIDE







## Ashcroft® Inc. – the experts in pressure and temperature measurement

Over 150 years ago, Edward Ashcroft saw the need for safer, more sophisticated pressure and temperature instruments for use in the emerging steam industry. In response, he introduced a then-revolutionary new Bourdon tube pressure gauge.

The rest is history.

Times continue to change and so do the needs of industry. Products manufactured by Ashcroft Inc. have become the benchmark in pressure and temperature measurement and include gauges, thermometers, switches, transducers, transmitters, instrument isolators and diaphragm seals and control and calibration equipment.

Specified around the world for the most demanding requirements, these instruments are widely recognized under the brand names Ashcroft,® Heise,® Willy,® and Weksler.® And you can find them in wastewater treatment facilities, biotech and pharmaceutical labs, medical applications, semiconductor facilities, refineries, power generation plants, food processing plants, pulp and paper mills, chemical manufacturing plants and the host of support companies that serve these industries.

Our team consists of experts ready to help resolve even the most difficult applications and technical issues. If you require broader

specifications than our standard product line offers, our engineers, technical staff and product marketing specialists can work with you to custom fit the right product to the job. Our customer service representatives are highly trained to answer product application questions, offer competitive product cross references and work closely with you to help meet your goals.

We maintain an extensive network of field and in-house sales personnel, local representatives and distributors to ensure you receive quick product delivery and service. Along with our “partner” representatives we offer product training and education, facility surveys, calibration services, seal assembly and answers to your application questions.

Safety is a critical issue, and our instrument audit can improve the safety of your plant. Industry surveys indicate that 20% to 30% of customers’ instruments are misapplied and fail prematurely due to pulsation and vibration, allowing the process media or liquid fill to escape and cause environmental damage or even harm those nearby. Experts from Ashcroft Inc. can help identify areas of concern before they become problems. This important service will help prevent accidents, avoid misapplications and save money and time.

As the leader in technology and innovation we design new products based on current and emerging market requirements as well as individual customer’s requirements. As the industry leader our “firsts” lead the way with breakthrough new product features and value added benefits for the customer.

**ASHCROFT® INC.**



EDISON

**DIGITAL GAUGES**

Type 2089, 2086, 2084 Test Gauge.....	6
Type 2074, 2174, 2274 Industrial Gauge .....	6
Type D1005PS General Purpose Gauge .....	6

**TEST INSTRUMENTS, TEST GAUGES & EQUIPMENT**

Type 1084 Test Gauge .....	6
Type 1082 Test Gauge .....	7
Type 2089, 2086, 2084 Digital Test Gauge .....	7
Type ATE-100 Portable Pressure/Temperature Calibrator .....	7
Type ST-2A Precision Benchtop Pressure/Temperature Gauge .....	7
Type 1305D Deadweight Tester .....	8
Type 1327D, 1327CM Gauge Comparator .....	8
Type PT LCD Precision Digital Pressure Indicator ...	8
Type AVC-1000 & 3000 Volume Controller .....	8
Type A4A Precision Dial Pressure Gauge .....	9

**PROCESS GAUGES**

Type 1279 Duragauge® Pressure Gauge.....	9
Type 1377 Duragauge® Pressure Gauge.....	9
Type 1379 Duragauge® Pressure Gauge.....	9
Type 2462 Pressure Gauge.....	10
Type 1259 Pressure Gauge.....	10
Type 2279 Duratran® Pressure Transmitter .....	10

**STAINLESS STEEL CASE & INDUSTRIAL GAUGES**

Type 1008S Pressure Gauge 40 & 50mm .....	11
Type 1008S Pressure Gauge 63 & 100mm .....	11
Type 1009 Duralife® Pressure Gauge 2 1/2", 3 1/2" ...	11
Xmitr™ X1009.....	11
Type 1009 Stainless Steel Case 4 1/2", 6".....	12
Type 1109 General Service Gauge .....	12
Type 1009, 1010, 1017, 1220 Hydraulic Gauges ..	12
Type 1009, 1010, 1017, 1220 Receiver Gauges.....	12
Type 1009, 1010, 1017, 1220 Refrigeration Gauge	13
Type 1010 General Service Gauge .....	13
Type 1017 General Service Gauge .....	13
Type 1220 General Service Gauge .....	13
Type 1020S Xmas Tree Gauge .....	14
Type 1038, 1339 Duplex Gauge.....	14
Type 1150H Reid Vapor Gauge.....	16
Type 1122 Gauge .....	17
Type 1187, 1188, 1189 LP Bellows Gauge.....	17
Type 1490 LP Diaphragm Gauge .....	17
Type 1495 LP Receiver Gauge .....	17

**DIFFERENTIAL GAUGES**

Type 1125, 1125A Differential Gauge.....	14
Type 1127, 1128 Differential Gauge.....	14
Type 1130 Differential Gauge.....	15
Type 1131 Differential Gauge.....	15
Type 1132 Differential Gauge.....	15
Type 1133 Differential Gauge.....	15

Type 1134 Differential Gauge .....	16
Type 5503 Differential Gauge .....	16
Type 5509 Differential Gauge .....	16

**DIGITAL/INDUSTRIAL GAUGES**

Type 2074, 2174, 2274 Industrial Gauge .....	18
--	----

**SANITARY GAUGES**

Type 1032 Fractional Sanitary Gauge .....	18
Type 1032 Sanitary Gauge .....	18
Type 1036 w/1037 Instrument Fitting.....	18
Xmitr™ X1009 .....	19

**COMMERCIAL GAUGES**

Type D1005PS General Purpose Digital Gauge.....	19
Xmitr™ X1005, X2001 Transmitter Gauge.....	19
Type 1005P, 1005, 1005S.....	19
Type 1001T Panel Gauge .....	20
Type 1008A/AL General Service Gauge.....	20
Type 3005/30005P Hydraulic Gauge.....	20
Type 1005M, XRG Agricultural Ammonia.....	20
Type 1005M, XR5 Refrigerant Ammonia .....	21
Type 1005P, XUL Sprinkler Service Gauge.....	21
Type 1007P, XOR Refrigeration Manifold .....	21
Type 2071 Contractor Gauge .....	21
Type 40/50 DDG Direct Drive Gauge .....	22
Type 23 DDG Minigauge® .....	22
Type 12/15 DDG Direct Drive Gauge .....	22
Type MFX Fire Extinguisher Gauge .....	22

**DIAPHRAGM SEALS/ INSTRUMENT ISOLATORS**

Type 100/200/300 .....	23
Type 101/201/301 .....	23
Type 102/202/302 .....	23
Type 103/203/303 .....	23
Type 104/204/304 .....	23
Type 105/205 .....	24
Type 106/206 .....	24
Type 107/207 .....	24
Type 108.....	24
Type 310/315 .....	24
Type 311.....	25
Type 312.....	25
Type 320/321 .....	25
Type 330.....	25
Type 400/401 .....	25
Type 402/403 .....	26
Type 500/501 .....	26
Type 702/703 .....	26
Type 740/741 .....	26
Type 80/81/85/86 .....	26

**TRANSDUCERS AND TRANSMITTERS**

GC51 Type Rangeable Pressure Transmitter.....	27
GC55 Wet/Wet Differential Pressure Transmitter ...	27
Xmitr™ X1005, X2001 .....	27
Xmitr™ X1009.....	28
A2 Explosion Proof Transmitters.....	28
T2 High Performance Pressure Transducer .....	28
G2 OEM Pressure Transducer.....	29
KM10 OEM Transducer .....	29
K1/K2 Series Industrial Transducer .....	29
K8 Series Transducer w/mV Signal.....	29
KX/KS Series Sanitary Transducers.....	30
GC52 Rangeable Wet/Wet DP Transmitter .....	30
CXLdp Series .....	30
DXLdp Series .....	30
RXLdp Series .....	31
XLdp Series .....	31
IXLdp Series.....	31
Type 2279 Duratran® Pressure Transmitters.....	31

**THERMOMETERS**

Pocket Test Commercial Thermometer .....	33
Industrial Bimetal Thermometer .....	33
Duratemp® Thermometer .....	33
Digital Thermometer .....	33

**PRESSURE & TEMPERATURE SWITCHES**

B Series Single Setpoint Watertight.....	35
B Series Single Setpoint Explosion Proof .....	35
L Series Dual Setpoint Watertight.....	35
P Series Dual Setpoint Watertight.....	35
G Series Watertight Stainless Steel .....	36
F Series Compact Explosion Proof Pressure .....	36
A Series Miniature Pressure Switches.....	36
N Series Electronic Pressure Switches.....	36
Differential Pressure Switch Actuator .....	37
ATEX Approval for Hazardous Locations .....	37
U.L. Listed Steam Limit Control .....	37
U.L. Listed Pressure Limit Control .....	37

## Digital Gauges

## Test Instruments

### TYPES 2089, 2086, 2084 PRECISION DIGITAL TEST GAUGE



<b>ACCURACY</b> ±0.05%, 0.10% or 0.25% of span
<b>CASE SIZE</b> 3"
<b>CASE MATERIAL</b> 300 Series stainless steel, electropolished
<b>WETTED MATERIALS</b> 316 stainless steel connection
<b>SOCKET SIZE</b> 1/4 NPT JIS, DIN, SAE, (others on application)
<b>CONNECTION</b> Lower (6 o'clock)
<b>RANGES</b> Vac., 5 psi thru 7000 psi including compound and absolute
<b>POWER SOURCE</b> Three AAA alkaline batteries
<b>BATTERY LIFE</b> > 1000 hrs.
<b>OPERATING TEMPERATURE</b> Temperature corrected from 0/150°F (-18/63°C)
<b>STORAGE TEMPERATURE</b> -40/180°F (-40/82°C)
<b>AGENCY APPROVALS</b> CE, EN 50082-1 (1997), FM, CSA

With total error band accuracy including temperature from 0/150°F (-18 to 63°C) applications include metrology labs, gas distribution and transmission and analog test gauge users.

### TYPES 2074, 2174, 2274 INDUSTRIAL DIGITAL GAUGE



<b>ACCURACY:</b> ±0.25% of span
<b>CASE SIZE</b> 3", 4 1/2"
<b>CASE MATERIAL</b> (3") 300 series stainless steel (4 1/2") fiberglass reinforced thermoplastic (4 1/2") black painted aluminum
<b>WETTED MATERIALS</b> 17-4 PH stainless steel sensor; 316 stainless steel socket
<b>SOCKET SIZE</b> 1/4 NPT, 1/2 NPT (4 1/2" case only)
<b>CONNECTION</b> Lower (6 o'clock)
<b>RANGES</b> Vac. and 15 psi thru 20,000 psi including compound
<b>POWER SOURCE</b> Battery (3") Two AA alkaline batteries (4 1/2") Two C alkaline batteries Loop powered 4-20mA Line powered, (12-36 Vdc, 1 amp)
<b>BATTERY LIFE</b> (3") >1000 hrs. (4 1/2") >3600 hrs.
<b>OPERATING TEMPERATURE</b> 14/140°F (-10/60°C)
<b>STORAGE TEMPERATURE</b> -4/158°F (-20/70°C)
<b>AGENCY APPROVALS</b> CE, EN 50082-1 (1997), FM, CSA, CENELEC-ATEX 100

Available with optional (1) or (2) SPDT switches and 4-20mA output, this gauge is ideal for many industrial applications. This product eliminates the need for unnecessary piping, switches and transducers.

### TYPE D1005PS GENERAL PURPOSE DIGITAL GAUGE



\*Protective Boot Optional

<b>ACCURACY</b> ±0.5% of span
<b>CASE SIZE</b> 2 1/2"
<b>CASE MATERIAL</b> Noryl®
<b>WETTED MATERIALS</b> 17-4 PH stainless steel sensor; 316 stainless steel socket
<b>SOCKET SIZE</b> 1/4 NPT
<b>CONNECTION</b> Lower (6 o'clock)
<b>RANGES</b> Vac. thru 19,999, including compound
<b>POWER SOURCE</b> Two AAA alkaline batteries
<b>BATTERY LIFE</b> 1000 hrs.
<b>OPERATING TEMPERATURE</b> 14/140°F (-10/60°C)
<b>STORAGE TEMPERATURE</b> -4/158°F (-20/70°C)
<b>AGENCY APPROVALS</b> CE, EN 61326 (1998) CE, EN 61326 Annex A (heavy industrial)

This product is an excellent choice for a wide variety of pressure measurement applications. When compared to mechanical gauges the D1005PS offers overall enhanced value.

### TYPE 1084 3" TEST GAUGE



<b>ACCURACY</b> ASME B 40.1 Grade 2A (±0.5% of span)
<b>DIAL SIZE</b> 3"
<b>CASE MATERIAL</b> 300 series polished stainless steel
<b>MATERIAL</b> 316 stainless steel
<b>SENSING ELEMENT</b> Bourdon tube
<b>CONNECTION</b> 1/4 NPT lower only
<b>RANGES</b> Vac. to 1000 psi

Ideal for use when a quality analog pocket test gauge is required.



## Test Instruments

1082 4 1/2", 6", 8 1/2" TEST GAUGE	TYPES 2089, 2086, 2084 PRECISION DIGITAL TEST GAUGES	TYPE ATE-100 LCD DIGITAL CALIBRATOR	ST-2A LCD DIGITAL INDICATOR
			
<b>ACCURACY</b> ASME B 40.1 Grade 3A ( $\pm 0.25\%$ of span)	<b>ACCURACY</b> $\pm 0.05\%$ , 0.10% or 0.25% of span	<b>PRESSURE MEASUREMENT ACCURACY</b> $\pm 0.025$ , 0.05 and 0.1% of span	<b>PRESSURE MEASUREMENT ACCURACY</b> $\pm 0.025$ , 0.05 and 0.1% of span
<b>DIAL SIZE</b> 4 1/2", 6", 8 1/2"	<b>CASE SIZE</b> 3"	<b>PRESSURE RANGES</b> 0/0.25 in. H <sub>2</sub> O through 0/10,000 psi	<b>PRESSURE RANGES</b> 0/0.25 in. H <sub>2</sub> O through 0/10,000 psi
<b>CASE MATERIAL</b> Aluminum, phenolic, polypropylene	<b>CASE MATERIAL</b> 300 Series stainless steel, electropolished	<b>PRESSURE TYPES</b> Gauge, compound, vacuum, absolute and differential	<b>PRESSURE TYPES</b> Gauge, compound, vacuum, absolute and differential
<b>WETTED MATERIAL</b> Bronze/brass, Monel	<b>WETTED MATERIALS</b> 316 stainless steel connection	<b>TEMPERATURE COMPENSATION</b> 20-120°F	<b>TEMPERATURE COMPENSATION</b> 20-120°F
<b>SENSING ELEMENT</b> Bourdon tube	<b>SOCKET SIZE</b> 1/4 NPT JIS, DIN, SAE (others on application)	<b>TEMPERATURE MEASUREMENT</b> Supports most common RTD-type temperature probes and thermocouples	<b>TEMPERATURE MEASUREMENT</b> Supports most common RTD-type temperature probes and thermocouples
<b>CONNECTION</b> 1/4 NPT (standard) and 1/2 NPT lower or back (optional)	<b>CONNECTION</b> Lower (6 o'clock), 3 and 9 o'clock	<b>DIMENSIONS</b> 7.88 in. (L) x 4.24 in. (W) x 3.25 in. (H)	<b>DIMENSIONS</b> 10.9 in. (L) x 6.74 in. (W) x 4.0 in. (H)
<b>RANGES</b> Vac. to 10,000 psi	<b>RANGES</b> Vac., 5 psi thru 7000 psi including compound and absolute	<b>WEIGHT</b> Max. 2.2 lbs. w/2 pressure modules installed	<b>PANEL CUTOUT</b> 6.56 in. x 3.53 in.
	<b>POWER SOURCE</b> Three AAA alkaline batteries	<b>CASE MATERIAL</b> High impact ABS	<b>WEIGHT</b> Max. 4.08 lbs. w/2 pressure modules installed
	<b>BATTERY LIFE</b> > 1000 hrs.	<b>SENSOR MODULE CAPACITY</b> 2 bays for Ashcroft AQS "Quick Select" sensor modules	<b>CASE MATERIAL</b> High impact ABS
	<b>OPERATING TEMPERATURE</b> Temperature corrected from 0/150°F (-18/63°C)	<b>DISPLAY</b> 2 line LCD, 0.037 in. height per line. Can display simultaneous readings from 2 modules	<b>SENSOR MODULE CAPACITY</b> 2 bays for Ashcroft AQS "Quick Select" sensor modules
	<b>STORAGE TEMPERATURE</b> -40/180°F (-40/82°C)	<b>ELECTRICAL CONNECTION</b> Miniature recessed banana jacks (one set of test leads provided with each ATE-100)	<b>DISPLAY</b> 2 line LCD, 0.037 in. height per line. Can display simultaneous readings from 2 modules.
	<b>AGENCY APPROVALS</b> CE, EN 50082-1 (1997), FM, CSA	<b>UPDATE RATE</b> 130 ms (nominal) with one sensor installed	<b>ELECTRICAL CONNECTION</b> Standard banana jacks
		<b>RESOLUTION</b> $\pm 0.002\%$ of span, 60,000 count (max)	<b>OPERATING TEMPERATURE RANGE</b> 32° to 120°F
		<b>DAMPING (Measurement Averaging)</b> Programmable averaging from zero through 16 consecutive readings	<b>UPDATE RATE</b> 130 ms (nominal) with one sensor installed
		<b>SERIAL INTERFACE</b> Type: RS-232 up to 9600 baud	<b>RESOLUTION</b> $\pm 0.002\%$ of span, 60,000 counts (max)
			<b>ELECTRICAL MEASUREMENTS</b> 0-50 mA or 0-30 Vdc
1/4% full scale accuracy for test and laboratory applications.	Superior accuracy for test and laboratory applications.	Field or laboratory precision pressure standard for calibrating or setting other instruments and devices. Also used for high accuracy temperature or pressure measurement in critical processes.	Laboratory precision pressure standard for calibrating or setting other instruments and devices. Also used for high accuracy temperature or pressure measurement in critical processes.

## Test Instruments

TYPE 1305D DEADWEIGHT TESTER	TYPE 1327D, 1327CM GAUGE COMPARATOR	MODEL PT, DUAL DISPLAY LCD DIGITAL INDICATOR	TYPE AVC-1000 & 3000 VOLUME CONTROLLER
			
<b>ACCURACY</b> $\pm 0.1\%$ of reading	<b>OPERATING PRESSURE</b> 0-10,000 psi (maximum) (0-70,000 kPa)	<b>PRESSURE MEASUREMENT ACCURACY</b> $\pm 0.025, 0.05$ and $0.1\%$ of span	<b>TYPE</b> AVC-1000 / AVC-3000
<b>OPERATING PRESSURE</b> 15 psi to 10,000 psi (100 kPa to 70,000 kPa)	<b>OPERATING MEDIA</b> Std.: SAE 20 weight automotive or machine oil Opt.: Phosphate-based or glycol fluids Distilled water for oxygen service	<b>PRESSURE RANGES</b> 0/0.25 in. H <sub>2</sub> O through 0/10,000 psi	<b>RANGE (psi)</b> vacuum-1000 / vacuum-3000
<b>OPERATING MEDIA</b> 1305D: SAE 20 weight automotive or machine oil	<b>O-RING MATERIAL</b> Standard: Buna N (D Series) Optional: Ethylene Propylene (DH Series)	<b>PRESSURE TYPES</b> Gauge, compound, vacuum, absolute and differential	<b>RESOLUTION (psi)</b> 0.00025 / 0.0005
<b>1305DH</b> Phosphate-based or glycol fluids	<b>RESERVOIR VOLUME</b> Approximately 1.5 pints (0.7 liter)	<b>TEMPERATURE MEASUREMENT</b> Supports most common RTD-type temperature probes	<b>VOLUME CHANGE (cubic inches)</b> 3.5 / 2.5
<b>O-RING MATERIAL</b> 1305D: Buna-N (D series)	<b>SPECIFICATIONS TYPE 1327DG</b>	<b>DIMENSIONS</b> 7.72 in. (L) x 6 in. (W) x 2.95 in. (H)	<b>MECHANICAL ROTATION (turns)</b> 31 / 61
<b>1305DH</b> Ethylene Propylene (DH Series)	<b>ACCURACY</b> $\pm 0.25\%$ F.S.	<b>PANEL CUTOUT</b> 5.4 in. x 2.68 in.	<b>PROOF PRESSURE (psi)</b> 2000 / 6000
<b>PISTON AND CYLINDER MATERIAL</b> Stainless steel	<b>GAUGE TYPE</b> Ashcroft 4½ inch Type 1082 gauges with temperature compensation	<b>WEIGHT</b> Depending on configuration Max. <4 lbs. w/2 sensors and battery pack	<b>BURST PRESSURE (psi)</b> 6000 min / 12,000 min
<b>WEIGHT MATERIAL</b> Non-magnetic die cast zinc	Special "CD-4" Certification package available (see Price Sheet TE/PS-1)	<b>CASE MATERIAL</b> High impact ABS	<b>OPERATING TEMPERATURE RANGE</b> 20-120°F / 20-120°F
<b>RESERVOIR VOLUME</b> Approximately 1.5 pints (0.7 liter)	<b>SPECIFICATIONS TYPE 1327CM</b>	<b>SENSOR CAPACITY</b> 2 bays for Ashcroft PPT sensors	<b>OPERATING MEDIA</b> Clean, dry noncorrosive gas such as compressed air or nitrogen
Special "CD-5" Certification package available (see Price Sheet TE/PS-1)	<b>ACCURACY</b> $\pm 0.1\%$ F.S.	<b>DISPLAY</b> 5 digit, 2 line LCD, 0.038 in. height per line. Can display simultaneous readings from 2 modules.	<b>CONSTRUCTION</b> Aluminum body, stainless steel, brass Teflon, Delrin and Buna N
	<b>GAUGE TYPE</b> Ashcroft 6-inch Type A4A with temperature compensation	<b>OUTPUT</b> Full function RS-232	
	<b>TEMPERATURE COMPENSATION</b> -25°F to +125°F (will maintain $\pm 0.1\%$ F.S. accuracy)	<b>OPTIONS</b> <i>Backlit Display; Built-in NiCad Rechargeable Batteries; Handle; Panel Mounting Brackets</i>	
		<b>OPERATING TEMPERATURE RANGE</b> 32° to 120°F	
		<b>TEMPERATURE COMPENSATION</b> 20-120°F	
		<b>UPDATE RATE</b> 130 ms (nominal) with one sensor installed	
		<b>RESOLUTION</b> $\pm 0.002\%$ of span, 60,000 counts (max)	
Primary deadweight pressure standard and hydraulic pressure source for calibration of other pressure instruments.	Uses either 0.25% or 0.1% "master gauges" and hydraulic pressure source for calibration of other pressure instruments.	Laboratory precision pressure standard for calibrating or setting other instruments and devices. Also used for high accuracy temperature or pressure measurement in critical processes.	Added to any pneumatic calibration system, the VC works as a "fine tune" device to achieve specific test points not easily attained with the use of a regulator alone. Used in the calibration of any pneumatic pressure instrument up to 3000 psi.



## Test Instruments

## Process Gauges

TYPE A4A PRECISION  
DIAL PRESSURE GAUGE

**ACCURACY**  
±0.10% of span – ASME B40.1, Grade 4A

**CASE**  
Cast aluminum solid front

**DIAL SIZE**  
6", 8 1/2", 12" & 16"

**POINTER TRAVEL**  
350° (15-30,000 psi)  
300° (40,000-50,000 psi)  
270° (60,000-100,000 psi)

**BOURDON TUBE**  
Bleeder tipped

**RANGES**  
Gauge, compound, vacuum & absolute  
0-15-0/100,000 psi

1279 DURAGAUGE®  
PRESSURE GAUGE

**ACCURACY**  
ASME B 40.1 Grade 2A (±0.5% of span)

**DIAL SIZE**  
4 1/2"

**CASE MATERIAL**  
Phenolic

**WETTED MATERIAL**  
316 stainless steel, bronze/brass, Monel

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
1/2 NPT (standard) lower or back  
1/4 NPT (optional)

**RANGES**  
Vacuum, 15 to 30,000 psi, compound

Usage requiring 1/2% full scale accuracy in chemical, petrochemical, refinery, oil production, other process, power and general industry.

1377 DURAGAUGE®  
PRESSURE GAUGE

**ACCURACY**  
ASME B 40.1 Grade 2A (±0.5% of span)

**DIAL SIZE**  
4 1/2", 6", 8 1/2"

**CASE MATERIAL**  
Aluminum

**WETTED MATERIAL**  
316 stainless steel, bronze/brass, Monel

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
1/2 NPT (standard) lower or back  
1/4 NPT (optional)

**RANGES**  
Vacuum, 15 to 30,000 psi, compound

Usage requiring 1/2% full scale accuracy in chemical, petrochemical, refinery, oil production, other process, power and general industry.

1379 DURAGAUGE®  
PRESSURE GAUGE

**ACCURACY**  
ASME B 40.1 Grade 2A (±0.5% of span)

**DIAL SIZE**  
4 1/2", 6", 8 1/2"

**CASE MATERIAL**  
Aluminum

**WETTED MATERIAL**  
316 stainless steel, bronze/brass, Monel, Inconel

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
1/2 NPT (standard) lower or back  
1/4 NPT (optional)  
1/4" HP connection over 30,000 psi

**RANGES**  
Vacuum, 15 to 100,000 psi, compound

Usage requiring 1/2% full scale accuracy in chemical, petrochemical, refinery, oil production, other process, power and general industry.

## Process Gauges

### 2462 DURAGAUGE®<sup>TM</sup> PRESSURE GAUGE



**ACCURACY**  
ASME B 40.1 Grade 2A ( $\pm 0.5\%$  of span)

**DIAL SIZE**  
6"

**CASE MATERIAL**  
Polypropylene

**WETTED MATERIAL**  
316 stainless steel, bronze/brass, steel, Monel

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
 $\frac{1}{2}$  NPT (standard) lower or back  
 $\frac{1}{4}$  NPT (optional)

**RANGES**  
Vacuum, 15 to 30,000 psi, compound

Usage requiring  $\frac{1}{2}\%$  full scale accuracy in chemical, petrochemical, refinery, oil production, other process, power and general industry.

### 1259 PROCESS PRESSURE GAUGE



**ACCURACY**  
ASME B 40.1 Grade 2A ( $\pm 0.5\%$  of span)

**DIAL SIZE**  
 $4\frac{1}{2}$ "

**CASE MATERIAL**  
Polypropylene

**WETTED MATERIAL**  
316 stainless steel, Monel

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
 $\frac{1}{2}$  NPT (standard) lower  
 $\frac{1}{4}$  NPT (optional)

**RANGES**  
Vacuum, 15 to 20,000 psi, compound

Usage requiring  $\frac{1}{2}\%$  full scale accuracy in chemical, petrochemical, refinery, oil production, other process, power and general industry.

### 2279 DURATRAN® PRESSURE TRANSMITTER



**ACCURACY**  
 $\pm 0.5\%$

**DIAL SIZE**  
 $4\frac{1}{2}$ " analog

**CASE MATERIAL**  
Phenolic

**WETTED MATERIAL**  
316 stainless steel, Monel

**SENSING ELEMENT**  
Bourdon tube





**CONNECTION – NPT**  
 $\frac{1}{2}$  NPT (standard) lower

**RANGES**  
Vacuum and compound, 12 to 20,000 psi

**ELECTRONIC OUTPUT**  
•  $\pm 0.5\%$  Accuracy  
• 4-20mA  
• FM Class I, Div. 2  
• Zero/Span adjust

Two instruments in one! Provides local indication and 4-20mA signal for many industrial applications.

## Stainless Steel Case & Industrial Gauges



1008S 40 & 50 mm PRESSURE GAUGE	1008S 63 & 100mm PRESSURE GAUGE	1009 2½" & 3½" DURALIFE® PRESSURE GAUGE	X1009 2½" & 3½" XMITR™ TRANSMITTER GAUGE
 <p><b>IN A RUSH?</b> ASHCROFT <b>GOLD SERVICE</b></p>	 <p><b>IN A RUSH?</b> ASHCROFT <b>GOLD SERVICE</b></p> <p><b>PLUS!</b> performance</p>	 <p><b>IN A RUSH?</b> ASHCROFT <b>GOLD SERVICE</b></p> <p><b>PLUS!</b> performance</p>	 <p><b>PATENTED</b></p> <p><b>NEW!</b></p> <p>CE LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</p>
<b>ACCURACY</b> ASME B 40.1 Grade B (±3-2-3% of span)	<b>ACCURACY</b> ASME B 40.1 Grade B (±3-2-3% of span)	<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)	<b>ACCURACY</b> Electrical output is 1% BFSI including non-linearity, hysteresis and non-repeatability. Gauge is ASME B40.1 Grade 1A 1%
<b>DIAL SIZE</b> 40mm, 50mm	<b>DIAL SIZE</b> 63mm, 100mm	<b>DIAL SIZE</b> 2½", 3½"	<b>DIAL SIZE</b> 2½", 3½"
<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL/INGRESS PROTECTION</b> Stainless steel IP50 (std.), IP65(XJL)
<b>WETTED MATERIAL</b> 316 stainless steel	<b>WETTED MATERIAL</b> 316L stainless steel	<b>WETTED MATERIAL</b> 316L Stainless steel	<b>WETTED MATERIAL</b> 316L stainless steel
<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube with patented transducer technology
<b>CONNECTION</b> ⅛ NPT lower or back ¼ NPT lower or back	<b>CONNECTION</b> ⅛ NPT lower or back ¼ NPT lower or back ½ NPT lower (100mm) JIS, DIN, BSP	<b>CONNECTION</b> ⅛ NPT lower or back ¼ NPT lower or back ½ NPT lower (3½") JIS, DIN, BSP	<b>CONNECTION</b> ⅛ and ¼ NPT, G ¼ lower
<b>RANGES</b> Vac. to 15,000 psi	<b>RANGES</b> Vac. to 15,000 psi	<b>RANGES</b> Vac. to 15,000 psi	<b>RANGES</b> Compound to 15,000 psi
<p>Applications include industrial compressors, valve indicators, firefighting equipment, measurement/control, metal working and hydraulic equipment. Especially suited for pneumatic controllers and transmitters.</p>	<p>Applications include industrial compressors, firefighting equipment, measurement/control, metal working, hydraulic equipment and panel builders.</p>	<p>For use on fluid power equipment in oil and gas production, construction, mining, machine tools, logging, pulp and paper, general industrial applications.</p>	<p>2 Instruments in 1. Breakthrough functionality and value. Stainless steel case, 4-20mA and voltage outputs, cable or Hirschmann conn. CE heavy industrial. Per EN61326, 1998 ANNEX A</p>

## Stainless Steel Case & Industrial Gauges

1009 4½" & 6" STAINLESS STEEL CASE	1109 4½" GENERAL SERVICE GAUGE	1009, 1010, 1017, 1220 HYDRAULIC GAUGES	1009, 1010, 1017, 1220 RECEIVER GAUGES
 <p>IN A RUSH? ASHCROFT GOLD SERVICE</p> <p>PLUS! Performance</p>	 <p>PLUS! Performance</p>	 <p>IN A RUSH? ASHCROFT GOLD SERVICE</p> <p>PLUS! Performance</p> <p>1010 GAUGE SHOWN</p>	 <p>IN A RUSH? ASHCROFT GOLD SERVICE</p> <p>1220 GAUGE SHOWN</p>
<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)	<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)	<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)	<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)
<b>DIAL SIZE</b> 4½", 6"	<b>DIAL SIZE</b> 4½"	<b>DIAL SIZE</b> 1009 – 4½", 6" 1010 – 4½", 6", 8½", 12" 1017 – 4½", 6" 1220 – 4½", 6", 8½"	<b>DIAL SIZE</b> 1009 – 4½", 6" 1010 – 4½", 6", 8½", 12" 1017 – 4½", 6" 1220 – 4½", 6", 8½"
<b>CASE MATERIAL</b> Stainless Steel	<b>CASE MATERIAL</b> Stainless Steel	<b>CASE MATERIAL</b> Stainless steel, aluminum, phenolic	<b>CASE MATERIAL</b> Stainless steel, aluminum, phenolic
<b>TUBE MATERIAL</b> Bronze, 316 stainless steel, Monel	<b>TUBE MATERIAL</b> SD – 316 stainless steel WD – Inconel	<b>TUBE MATERIAL</b> Bronze, 316 stainless steel, Monel	<b>TUBE MATERIAL</b> Bronze, 316 stainless steel, Monel
<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube
<b>CONNECTION</b> ¼ NPT lower or back ½ NPT lower or back	<b>CONNECTION</b> SD – ½ NPT lower, ¼ NPT lower (optional) WD – ¼ NPT lower high pressure	<b>CONNECTION</b> ¼ NPT lower or back ½ NPT lower or back	<b>CONNECTION</b> ¼ NPT lower or back ½ NPT lower or back
<b>RANGES</b> Vac. to 30,000 psi	<b>RANGES</b> SD – Vac. to 1500 psi / 2000-20,000 psi WD – 50,000-100,000 psi	<b>RANGES</b> Vac. to 30,000 psi	<b>RANGES</b> 3/15 and 3/27 psi
Stainless steel case Type 1009 applications include boilers, compressors, water blasting equipment, pharmaceutical and food processing equipment.	Stainless steel case Type 1109 applications include water jet or water blasting equipment, offshore platform, etc.	Uniquely designed for rigorous hydraulic services.	For monitoring pneumatic systems requiring percentage or square root readings.



## Stainless Steel Case & Industrial Gauges

1009, 1010, 1017, 1220 REFRIGERATION GAUGE	1010 4½", 6", 8½", 12" GENERAL SERVICE GAUGE	1017 4½", 6" GENERAL SERVICE GAUGE	1220 4½", 6", 8½" GENERAL SERVICE GAUGE
			
1010 GAUGE SHOWN			
<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)	<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)	<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)	<b>ACCURACY</b> ASME B 40.1 Grade 1A (±1% of span)
<b>DIAL SIZE</b> 1009 – 4½", 6" 1010 – 4½", 6", 8½", 12" 1017 – 4½", 6" 1220 – 4½", 6", 8½"	<b>DIAL SIZE</b> 4½", 6", 8½", 12"	<b>DIAL SIZE</b> 4½", 6"	<b>DIAL SIZE</b> 4½", 6", 8½"
<b>CASE MATERIAL</b> Stainless steel, aluminum, phenolic	<b>CASE MATERIAL</b> Stainless steel, aluminum, phenolic	<b>CASE MATERIAL</b> Stainless steel, aluminum, phenolic	<b>CASE MATERIAL</b> Stainless steel, aluminum, phenolic
<b>TUBE MATERIAL</b> Bronze, stainless steel	<b>TUBE MATERIAL</b> Bronze, stainless steel, Monel	<b>TUBE MATERIAL</b> Bronze, stainless steel, Monel	<b>TUBE MATERIAL</b> Bronze, stainless steel, Monel
<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bourdon tube
<b>CONNECTION<sup>(1)</sup></b> ¼ NPT lower or back ½ NPT lower or back	<b>CONNECTION</b> ¼ NPT lower or back ½ NPT lower or back	<b>CONNECTION</b> ¼ NPT back ½ NPT back	<b>CONNECTION</b> ¼ NPT lower or back ½ NPT lower or back
<b>RANGES</b> 30 in.Hg Vac/150 psi, 30 in.Hg Vac/300 psi	<b>RANGES</b> Vac. to 30,000 psi	<b>RANGES</b> Vac. to 30,000 psi	<b>RANGES</b> Vac. to 30,000 psi
(1) 1017 back connect only			
For use on refrigeration equipment utilizing ammonia, freon or other refrigerants.	General industrial applications requiring larger dials. Applications include oil monitoring, repair and compressors, etc.	General industrial applications, large dials for easier readings. used on pumps, air or oil monitoring, etc.	General industrial applications, large dials for easier readings. used on pumps, air or oil monitoring, etc.

## Stainless Steel Case & Industrial Gauges

## Differential Gauges

**1020S 4½" XMAS TREE GAUGE**



**ACCURACY**  
ASME B 40.1 Grade 1A (±1% of span)

**DIAL SIZE**  
4½"

**CASE MATERIAL**  
Stainless steel

**TUBE MATERIAL**  
316 stainless steel

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
Lower

**RANGES**  
1000/20,000 psi – ½ NPT, ¼ NPT

Uniquely designed to meet rugged oil field applications.

**1038, 1339 3½," 4½" DUPLEX GAUGE**



1038 GAUGE SHOWN

**ACCURACY**  
ASME B 40.1 Grade A (±2-1-2% of span)

**DIAL SIZE**  
3½," 4½"

**CASE MATERIAL**  
Aluminum, cast iron

**TUBE MATERIAL**  
Bronze

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
Lower/back

**RANGES**  
1038A – 3½," 4½" – ¼ NPT 30/1000 psi  
1339A – 4½," – ¼ NPT 30/1000 psi  
Back conn. only

Uniquely designed to indicate two related pressures on the same dial.

**1125, 1125A 4½" DIFFERENTIAL GAUGE**



**ACCURACY**  
ASME B 40.1 Grade A (±2-1-2% of span)

**DIAL SIZE**  
4½," 6"

**CASE MATERIAL**  
Aluminum

**TUBE MATERIAL**  
Bronze

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
Lower/back

**RANGES**  
1125 – 4½," 6"<sup>(1)</sup> – ¼ NPT 20/1000 psi  
1125A – 4½," 6"<sup>(1)</sup> – ¼ NPT 10/0/10 psi-  
500/0/500 psi

<sup>(1)</sup> Lower connect only

Application include fills, monitors, flow, leak and level measurements.

**1127, 1128 4½," 6" DIFFERENTIAL GAUGES**



**ACCURACY**  
ASME B 40.1 Grade A (±2-1-2% of span)

**DIAL SIZE**  
4½," 6"

**CASE MATERIAL**  
Aluminum

**TUBE MATERIAL**  
316 stainless steel

**SENSING ELEMENT**  
Bourdon tube

**CONNECTION**  
Lower

**RANGES**  
1127 – 4½," 6" – ¼ NPT 10/1000 psi  
1128 – 4½," 6" – ¼ NPT 10/0/00 psi-  
400/0/400 psi


Application include fills, monitors, flow, leak and level measurements.

## Differential Gauges

1130 2", 2½", 3½", 4", 4½", 6" DIFFERENTIAL GAUGE	1131 2", 2½", 3½", 4", 4½", 6" DIFFERENTIAL GAUGE	1132 2½", 3½", 4", 4½", 6" DIFFERENTIAL GAUGE	1133 3½", 4", 4½", 6" DIFFERENTIAL GAUGES
 <b>EXPLOSION PROOF SWITCHES AVAILABLE</b>	 <b>EXPLOSION PROOF SWITCHES AVAILABLE</b>	 <b>EXPLOSION PROOF SWITCHES AVAILABLE</b>	
<b>ACCURACY</b> ±2% ascending	<b>ACCURACY</b> ±2% ascending	<b>ACCURACY</b> ±2% ascending	<b>ACCURACY</b> ±2% ascending
<b>DIAL SIZE</b> 2", 2½", 3½", 4", 4½", 6"	<b>DIAL SIZE</b> 2½", 3½", 4", 4½", 6"	<b>DIAL SIZE</b> 2½", 3½", 4", 4½", 6"	<b>DIAL SIZE</b> 3½", 4", 4½", 6"
<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Stainless steel
<b>BODY MATERIAL</b> Aluminum, brass, stainless steel	<b>BODY MATERIAL</b> Aluminum, brass, stainless steel	<b>BODY MATERIAL</b> Aluminum, brass, stainless steel	<b>BODY MATERIAL</b> Aluminum, stainless steel
<b>SENSING ELEMENT</b> Piston	<b>SENSING ELEMENT</b> Rolling diaphragm	<b>SENSING ELEMENT</b> Convuluted diaphragm	<b>SENSING ELEMENT</b> Convuluted diaphragm
<b>CONNECTION</b> In-line, lower, back	<b>CONNECTION</b> In-line, lower, back	<b>CONNECTION</b> In-line, lower, back	<b>CONNECTION</b> In-line, lower, back
<b>RANGES</b> 0-5 psid to 150 psid	<b>RANGES</b> 0-5 psid to 100 psid	<b>RANGES</b> 0-1 psid to 60 psid (including inches of water ranges)	<b>RANGES</b> 0-1 IWD to 25 IWD
Applications include filter monitoring, flow, leak and level measurement. High pressure, high differential with migration.	Applications include filter monitoring, flow, leak and level measurement. High pressure, high differential, no migration.	Applications include filter monitoring, flow, leak and level measurement. High pressure, high differential, no migration.	Applications include filter monitoring, flow, leak and level measurement. High pressure, high differential, no migration.

## Differential Gauges

## Stainless Steel Case & Industrial Gauges

1134 4½" DIFFERENTIAL GAUGE	5503 100mm & 160mm DIFFERENTIAL GAUGE	5509 100mm & 160mm DIFFERENTIAL GAUGE	1150H 4½" REID VAPOR GAUGE
			
<b>ACCURACY</b> ±2% ascending	<b>ACCURACY</b> ±1.6% of span	<b>ACCURACY</b> ±2.5% of span	<b>ACCURACY</b> ASME B 40.1 Grade 2A (±0.5% of span)
<b>DIAL SIZE</b> 4½"	<b>DIAL SIZE</b> 100mm, 160mm	<b>DIAL SIZE</b> 100mm, 160mm	<b>DIAL SIZE</b> 4½"
<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Aluminum
<b>BODY MATERIAL</b> Glass filled nylon	<b>SENSING MATERIAL</b> 316 stainless steel	<b>SENSING MATERIAL</b> 316 stainless steel	<b>TUBE MATERIAL</b> 316 stainless steel
<b>SENSING ELEMENT</b> Convolute diaphragm	<b>SENSING ELEMENT</b> Diaphragm	<b>SENSING ELEMENT</b> Diaphragm	<b>SENSING ELEMENT</b> Bourdon tube
<b>CONNECTION</b> Dual (In-line or back)	<b>CONNECTION</b> Lower	<b>CONNECTION</b> Lower	<b>CONNECTION</b> ¼ NPT lower
<b>RANGES</b> 0-0.6 IWD to 60 IWD	<b>RANGES</b> 0-16 IWD to 400 psid	<b>RANGES</b> 0-10 IWD to 400 psid	<b>RANGES</b> 15/600 psi
Applications include fume hoods, air handlers, filter monitoring, flow and level. Inches of water with no migration.	Applications include filter monitoring, flow, leak and level measurement requiring high recovery, all stainless steel.	Applications include filter monitoring, flow, leak and level measurement requiring high recovery, all stainless steel.	Uniquely designed for testing petroleum products with the Reid vapor process.



## Stainless Steel Case & Industrial Gauges

1122 2½" GAUGE	1187, 1188, 1189 LP BELLOWS GAUGES	1490 2½", 3½" LP DIAPHRAGM GAUGE	1495 2½", 3½" LP RECEIVER GAUGE
	 1188 GAUGE SHOWN 		
<b>ACCURACY</b> ASME B 40.1 Grade A (±2-1-2% of span)	<b>ACCURACY</b> ASME B 40.1 Grade A (±2-1-2% of span)	<b>ACCURACY</b> ASME B 40.1 Grade A (±2-1-2% of span)	<b>ACCURACY</b> ASME B 40.1 Grade A (±2-1-2% of span)
<b>DIAL SIZE</b> 2½"	<b>DIAL SIZE</b> 1187 <sup>(1)</sup> – 4½" 1188 – 4½" 1189 <sup>(2)</sup> – 4½", 6"	<b>DIAL SIZE</b> 2½", 3½"	<b>DIAL SIZE</b> 2½", 3½"
<b>CASE MATERIAL</b> Stainless steel	<b>CASE MATERIAL</b> Aluminum, phenolic	<b>CASE MATERIAL</b> Polysulfone	<b>CASE MATERIAL</b> Polysulfone
<b>TUBE MATERIAL</b> Stainless steel	<b>TUBE MATERIAL</b> Brass, 316 stainless steel, Monel	<b>WETTED MATERIAL</b> Copper, Brass, Polysulfone, RTV, Silicone	<b>WETTED MATERIAL</b> Copper, Brass, Polysulfone, RTV, Silicone
<b>SENSING ELEMENT</b> Bourdon tube	<b>SENSING ELEMENT</b> Bellows	<b>SENSING ELEMENT</b> Diaphragm	<b>SENSING ELEMENT</b> Diaphragm
<b>CONNECTION</b> ¼ NPT lower	<b>CONNECTION</b> 1187 – ¼, ½ NPT back 1188 – ¼, ½ NPT lower or back 1189 – ¼, ½ NPT lower	<b>CONNECTION</b> ⅛ NPT lower or back ¼ NPT lower or back Hose barb	<b>CONNECTION</b> ⅛ NPT lower or back ¼ NPT lower or back Hose barb
<b>RANGES</b> 15/1000 psi	<b>RANGES</b> 10 in.H <sub>2</sub> O to 10 psi including vacuum and compound	<b>RANGES</b> 0/10 in.H <sub>2</sub> O to 0/15 psi including vacuum and compound	<b>RANGES</b> 0-100%, 0-10 sq rt 0/10 sq rt /0-100 linear
Applications include compressors, pumps and turbines.	Low pressure monitoring for general industrial applications on air, liquids or gases.	Low pressure monitoring of gases including ovens, burners or material applications.	Low pressure monitoring of pneumatic or air handling systems requiring printout or square root readings.

## Digital Industrial Gauges

## Sanitary Gauges

### TYPES 2074, 2174, 2274 INDUSTRIAL DIGITAL GAUGE



**ACCURACY:**  
±0.25% of span

**CASE SIZE**  
3", 4 1/2"

**CASE MATERIAL**  
(3") 300 series stainless steel  
(4 1/2") fiberglass reinforced thermoplastic  
(4 1/2") black painted aluminum

**WETTED MATERIALS**  
17-4 PH stainless steel sensor;  
316 stainless steel socket

**SOCKET SIZE**  
1/4 NPT, 1/2 NPT (4 1/2" case only)  
(others on application)

**CONNECTION**  
Lower (6 o'clock), 3, 9 and 12 o'clock

**RANGES**  
Vac., 15 to 20,000 psi including compound

**POWER SOURCE**  
Battery  
(3") Two AA alkaline batteries  
(4 1/2") Two C alkaline batteries  
Loop powered 4-20mA  
Line powered, (12-36 Vdc, 1 amp)

**BATTERY LIFE**  
(3") >1000 hrs.  
(4 1/2") >3600 hrs.

**OPERATING TEMPERATURE**  
14/140°F (-10/60°C)

**STORAGE TEMPERATURE**  
-4/158°F (-20/70°C)

**AGENCY APPROVALS**  
CE, EN 50082-1 (1997), FM, CSA,  
CENELEC-ATEX 100

Available with optional (1) or (2) SPDT switches and 4-20mA output, this gauge is ideal for many industrial applications. This product eliminates the need for unnecessary instrument T's, when switches and/or 40-20mA output is a requirement.

### X1032 XMITR™ SANITARY TRANSMITTER GAUGE



**ACCURACY**  
Electrical output is 1% BFSL including non-linearity, hysteresis and non-repeatability. Gauge is ASME B40.1. 1.5% F.S. 100 psi and above, 2% below 100 psi

**DIAL SIZE**  
2 1/2", 3 1/2"

**CASE MATERIAL/INGRESS PROTECTION**  
Stainless steel, IP50 (std.). Option IP65 (XLJ)

**WETTED PARTS**  
Electro polished 12 to 20 RA surface finish  
316L stainless steel

**SENSING ELEMENT**  
Bourdon tube with patented transducer technology

**MOUNTING CONNECTION**  
Lower (1 1/2" and 2" Tri-Clover)

**RANGES**  
Compound to 1000 psi

Clean-in-place (CIP)  
Steam-in-place (SIP)  
3A sanitary standard (3A)

Sanitary pharmaceutical, biotech or food applications requiring Tri-Clover type fittings and highly polished stainless steel surfaces.

### TYPE 1032 FRACTIONAL SANITARY GAUGE



**ACCURACY**  
±3% upscale accuracy; up to ±5% downscale accuracy

**DIAL SIZE**  
2"

**CASE & RING MATERIAL**  
300 series stainless steel

**TUBE & SOCKET MATERIAL**  
316 stainless steel

**WETTED PARTS**  
Electropolished 12 to 20RA surface finish  
(stainless steel)

**MOUNTING CONNECTION**  
Lower (3/4" Tri-Clover)

**RANGES**  
30# thru 600#, including compound  
Meets EN 10204 : 2004 3.1 requirement for material traceability; documents provided as standard

Sanitary pharmaceutical, biotech or food applications requiring a compact 3/4 Tri-Clover fitting with highly polished stainless steel surfaces.

### TYPE 1032 SANITARY GAUGE



**ACCURACY**  
2 1/2", 3 1/2", 4 1/2" - ±1.5% F.S. for pressure ranges 100 psi and above. ±2.0% F.S. for vacuum, compound and ranges below 100 psi

**DIAL SIZE**  
2 1/2", 3 1/2", 4 1/2"

**CASE & RING MATERIAL**  
300 series stainless steel

**TUBE & SOCKET MATERIAL**  
316 stainless steel

**WETTED PARTS**  
Electropolished 12 to 20 RA surface finish  
(stainless steel)

**MOUNTING CONNECTION**  
Lower, back (1 1/2" or 2" Tri-Clover)

**RANGES**  
15# thru 1000#, including compound and vacuum

Meets EN 10204 : 2004 3.1 requirement for material traceability; documents provided as standard

Sanitary pharmaceutical, biotech or food applications requiring Tri-Clover type fittings and highly polished stainless steel surfaces.

## Sanitary Gauges

## Commercial Gauges

TYPE 1036 SANITARY GAUGE  
with TYPE 1037 SANITARY  
INSTRUMENT FITTING

Clamp not provided. User installed.

**ACCURACY**

±1.5% F.S. for pressure ranges 100 psi and above. ±2.0% F.S. for vacuum, compound and ranges below 100 psi

**DIAL SIZE**

3 1/2"

**CASE & RING MATERIAL**

300 series stainless steel

**TUBE & SOCKET MATERIAL**

316 stainless steel

**WETTED PARTS**

Electropolished 12 to 20 RA surface finish (stainless steel)

**MOUNTING CONNECTION**

Lower, back (1 1/2" Tri-Clover)

**RANGES**

15# thru 1000#, including compound and vacuum

**TYPE 1037 INSTRUMENT FITTING****CONSTRUCTION**

316 L stainless steel

**WETTED PARTS**

Electropolished 12 to 20RA surface finish

**MOUNTING CONNECTION**

(1 1/2" thru 2" Tri-Clover)

**HEAT NUMBER**

Stamped on fitting

Sanitary pharmaceutical, biotech or food applications requiring Tri-Clover type fittings with zero deadleg and highly polished stainless steel surfaces.

TYPE D1005PS GENERAL  
PURPOSE DIGITAL GAUGE

\*Protective Boot Optional

**ACCURACY**

±0.5% of span

**CASE SIZE**

2 1/2"

**CASE MATERIAL**

Noryl®

**WETTED MATERIALS**

17-4 PH stainless steel sensor;  
316 stainless steel socket

**SOCKET SIZE**

1/4 NPT

**CONNECTION**

Lower (6 o'clock), 3, 9 and 12 o'clock

**RANGES**

Vac. thru 19,999, including compound

**POWER SOURCE**

Two AAA alkaline batteries

**BATTERY LIFE**

1000 hrs.

**OPERATING TEMPERATURE**

14/140°F (-10/60°C)

**STORAGE TEMPERATURE**

-4/158°F (-20/70°C)

**AGENCY APPROVALS**

CE, EN 61326 (1998)  
CE, EN 61326 Annex A (heavy industrial)

This product is an excellent choice for a wide variety of pressure measurement applications. When compared to mechanical gauges the D1005PS offers overall enhanced value.

TYPE X1005, TYPE X2001  
XMITR™ TRANSMITTER GAUGE

PATENTED



CE  
LOOK FOR THESE AGENCY  
MARKS ON OUR PRODUCTS

**ACCURACY**

Electrical output is 1% BFSL including non-linearity, hysteresis and non-repeatability. Gauge is ASME B40.100 Grade B (±3-2-3% of span)

**DIAL SIZE**

Type X1005 2"  
Type X2001 2 1/2", 3 1/2"

**CASE MATERIAL/INGRESS PROTECTION**

Stainless steel  
Type 1005, IP54  
Type 2001, IP43 standard, IP54 (XLJ)

**WETTED MATERIAL**

Bronze/brass

**SENSING ELEMENT**

Bourdon tube with patented transducer technology

**CONNECTION**

1/8 and 1/4 NPT, G 1/4 lower

**RANGES**

Compound to 600 psi

2 Instruments in 1. Breakthrough functionality and value. Stainless steel case, 4-20mA and voltage outputs, cable or Hirschmann conn. CE heavy industrial. Per EN61326, 1998 ANNEX A

## TYPE 1005P/1005/1005S

**ACCURACY**

ASME B 40.100 Grade B (±3-2-3% of span)

**DIAL SIZE**

1 1/2", 2", 2 1/2", 3 1/2"  
(4 1/2" available with steel case/ring and plastic window, Type 1000)

**CASE MATERIAL**

1005P – ABS, black  
1005 – Black painted steel  
1005S – Stainless steel (1 1/2" & 2" only)  
Optional, color other than black, vent hole, panel mount sleeve for 1005P back connect

**WETTED MATERIAL**

Bronze/brass. Optional sockets, nickel plated, Teflon taped, top or side connections, throttle plugs

**SENSING ELEMENT**

Bourdon tube; Ashcroft patented PowerFlex™ movement

**CONNECTION**

1/8 and 1/4 NPT back and lower. (1 1/2" available in 1/8 NPT lower and back only; 4 1/2" Type 1000 available in 1/4 NPT lower only)

**RANGES**

Vac.-6000 psi and compound\*

\*All ranges listed may not be available in all sizes/connections. Please consult individual spec sheets.





Applications include compressors, filter regulators, medical equipment, automotive diagnostic, beverage dispensing, industrial machinery and a variety of other applications.

## Commercial Gauges

TYPE 1001T PANEL GAUGE	TYPE 1008A/AL GENERAL SERVICE GAUGE	TYPE 3005/3005P HYDRAULIC GAUGE	TYPE 1005M, XRG AGRICULTURAL AMMONIA
			
<b>ACCURACY</b> ASME B 40.100 Grade B ( $\pm 3-2-3\%$ of span)	<b>ACCURACY</b> ASME B 40.100 Grade B ( $\pm 3-2-3\%$ of span)	<b>ACCURACY</b> ASME B 40.100 Grade B ( $\pm 3-2-3\%$ of span)	<b>ACCURACY</b> ASME B 40.100 Grade B ( $\pm 3-2-3\%$ of span)
<b>DIAL SIZE</b> 1½", 2", 2½", 3½"	<b>DIAL SIZE</b> 63mm (2½"), 100mm (4")	<b>DIAL SIZE</b> 63mm (2½")	<b>DIAL SIZE</b> 2½"
<b>CASE MATERIAL</b> Black painted steel	<b>CASE &amp; RING MATERIAL</b> 304 stainless steel, dry, liquid filled or field fillable	<b>CASE MATERIAL</b> <b>3005</b> – 304 stainless steel, dry, liquid filled or field fillable <b>3005P</b> – Black ABS dry or glycerine filled	<b>CASE MATERIAL</b> Black painted steel <i>Optional, stainless clad aluminum (Type 1005SM)</i>
<b>WETTED MATERIAL</b> Bronze/brass.	<b>WETTED MATERIAL</b> Bronze/brass	<b>WETTED MATERIAL</b> Bronze/brass	<b>WETTED MATERIAL</b> 316 stainless steel/steel
<b>SENSING ELEMENT</b> Bourdon tube; Ashcroft patented PowerFlex™ movement	<b>SENSING ELEMENT</b> Bourdon tube; Ashcroft patented PowerFlex™ movement	<b>SENSING ELEMENT</b> Bourdon tube; Ashcroft patented PowerFlex™ movement	<b>SENSING ELEMENT</b> Bourdon tube; Ashcroft patented PowerFlex™ movement
<b>CONNECTION</b> ½ NPT back, ¼ NPT back (1½" not available in ¼ NPT)	<b>CONNECTION</b> ¼ NPT lower and back <i>Optional, metric and SAE connection</i>	<b>CONNECTION</b> <b>3005</b> – ¼ NPT lower and back <b>3005P</b> – ¼ NPT lower <i>Optional, metric and SAE connection</i>	<b>CONNECTION</b> ¼ NPT lower <i>Optional, 0.020" orifice stainless steel throttle plug</i>
<b>RANGES</b> Vac.-6000 psi and compound*	<b>RANGES</b> Vac.-15,000 psi and compound	<b>RANGES</b> Vac.-15,000 psi and compound	<b>RANGES</b> 0/60 psi, 0/150 psi, 0/400 psi
<b>Note:</b> For panel mount refrigeration gauge (recovery, recycling) specify 1001T, XRR gauge  *All ranges may not be available in all ranges/connections. Please consult individual spec sheets.			
Applications include instrument panels, air-conditioning equipment, air and gas compressors, machine tools and a variety of other applications.	Applications include hydraulic systems, machine tools, pressure washers/sprayers and a variety of other applications.	Applications include hydraulic systems, machine tools, pressure washers/sprayers, compressors, irrigation equipment and a variety of other applications.	This product was designed to withstand rugged agricultural applications. Features include stainless tube and socket, in addition to glass window, necessary for anhydrous ammonia applications.



## Commercial Gauges

TYPE 1005M, XR5 REFRIGERANT AMMONIA	TYPE 1005P, XUL SPRINKLER SERVICE GAUGE	TYPE 1007P, XOR REFRIGERATION MANIFOLD	TYPE 2071 CONTRACTOR GAUGE
			
<b>ACCURACY</b> ASME B 40.100 Grade B ( $\pm 3$ -2-3% of span)	<b>ACCURACY</b> ASME B 40.100 Grade B ( $\pm 3$ -2-3% of span)	<b>ACCURACY</b> $\pm 1\%$ at zero, $\pm 2\%$ three fourths of scale, $\pm 5\%$ last fourth of scale	<b>ACCURACY</b> ASME B 40.100 Grade A ( $\pm 2$ -1-2% of span)
<b>DIAL SIZE</b> 2 1/2", 3 1/2"	<b>DIAL SIZE</b> 3 1/2"	<b>DIAL SIZE</b> 2 1/2"	<b>DIAL SIZE</b> 4 1/2"
<b>CASE MATERIAL</b> Black painted steel <i>Optional, ABS (Type 1005PM); stainless clad aluminum (Type 1005SM)</i>	<b>CASE MATERIAL</b> ABS/polycarbonate blend	<b>CASE MATERIAL</b> ABS, red (high pressure) ABS, blue (low pressure) <i>Optional, black, ABS</i>	<b>CASE &amp; RING MATERIAL</b> Aluminum with back-flange case, painted black; chrome plated ring
<b>WETTED MATERIAL</b> 316 stainless steel/steel	<b>WETTED MATERIAL</b> Bronze/brass	<b>WETTED MATERIAL</b> Bronze/brass	<b>WETTED MATERIAL</b> Bronze/brass soldered, siphon required for steam service
<b>SENSING ELEMENT</b> Bourdon tube; Ashcroft patented PowerFlex™ movement	<b>SENSING ELEMENT</b> Bourdon tube; Ashcroft patented PowerFlex™ movement	<b>SENSING ELEMENT</b> Bourdon tube; Ashcroft patented PowerFlex™ movement with Flutter Guard™	<b>SENSING ELEMENT</b> Bourdon tube; Ashcroft patented PowerFlex™ movement
<b>CONNECTION</b> 1/4 NPT lower	<b>CONNECTION</b> 1/4 NPT lower	<b>CONNECTION</b> 1/8 NPT lower	<b>CONNECTION</b> 1/4 NPT lower <i>Optional, throttle plugs</i>
<b>RANGES</b> 30 in.Hg Vac/0/150 psi, 30 in.Hg Vac/0/300 psi with equivalent ammonia temperature scales	<b>RANGES</b> 0-300 psi (water), 0-80 psi retard to 250 psi (air)	<b>RANGES</b> Vac/0/120 psi retard to 250 psi, 0/500 psi Vac/0/500 psi retard to 800 psi, 0/800 psi <i>Optional, alternate refrigerant ranges</i>  <b>Note:</b> for panel mount refrigeration gauges (recovery, recycling) see Type 1001T gauge. Specify 1001T, XRR gauge	<b>RANGES</b> Vac-600 psi and compound
This product was designed to meet the requirements of refrigerant ammonia applications. Features include enhanced leak integrity plus dual scale (psi/temp) dial necessary for these applications.	These gauges are UL-393 listed, UL of Canada listed and FM approved for fire protection sprinkler service for either water or air systems.	Typical applications include checking or servicing refrigerant levels in automotive, residential or industrial air-conditioning units; refrigerant recovery and reclamation units; refrigerant transport systems and large scale air-conditioning and chilling equipment.	These gauges are designed to meet the needs of heating, ventilating, plumbing and air-conditioning contractors.

## Commercial Gauges

TYPE 40DDG/50DDG DIRECT DRIVE GAUGE	TYPE 23DDG MINIGAUGE® PRESSURE GAUGE	TYPE 12DDG/15DDG DIRECT DRIVE GAUGE	TYPE MFX FIRE EXTINGUISHER GAUGE
			
<b>ACCURACY</b> ASME B 40.100 Grade B ( $\pm 3-2-3\%$ of span)	<b>ACCURACY</b> $\pm 5\%$ of span	<b>ACCURACY</b> Standard: $\pm 2\%$ at setpoint (setpoint is normally 50% of range) UL listed: $\pm 3.5\%$ of span of middle three-fifths of scale	<b>ACCURACY</b> Conforms to applicable UL specs*
<b>DIAL SIZE</b> 40mm (1 1/2") or 50mm (2")	<b>DIAL SIZE</b> 23mm (0.906")	<b>DIAL SIZE</b> 1 1/4", 1 1/2"	<b>DIAL SIZE</b> 1 1/4", 1 1/2"
<b>CASE MATERIAL</b> ABS polycarbonate blend, black	<b>CASE MATERIAL</b> ABS blend, black	<b>CASE MATERIAL</b> Stainless steel, sealed	<b>CASE MATERIAL</b> Stainless steel, sealed
<b>WETTED MATERIAL</b> Beryllium copper coil, silicone dampened Integral ABS polycarbonate blend socket <i>Optional, 1/8 NPT or 1/4 NPT brass, throttle plug</i>	<b>WETTED MATERIAL</b> Beryllium copper tube/brass socket	<b>WETTED MATERIAL</b> Beryllium copper tube/brass socket	<b>WETTED MATERIAL</b> Beryllium copper/brass
<b>SENSING ELEMENT</b> Spiral wound Bourdon tube	<b>SENSING ELEMENT</b> Spiral wound Bourdon tube	<b>SENSING ELEMENT</b> Spiral wound Bourdon tube <i>Optional, silicone dampened tube, silicone-filled tube</i>	<b>SENSING ELEMENT</b> Spiral wound Bourdon tube <i>Optional, silicone-filled tube</i> <i>Spiral tube, beryllium copper</i>
<b>CONNECTION</b> 40mm – 1/8 NPT back 50mm – 1/8 NPT or 1/4 NPT back	<b>CONNECTION</b> 1/8 NPT back with 15mm (5/8") wrench flats. <i>Optional, throttle plugs, PT 1/8" (JIS) and R 1/8" (BSPT) threads</i>	<b>CONNECTION</b> 1/8 NPT back, safety plug in 1500 psi-4000 psi ranges. <i>Optional, 1/4 NPT back, throttle plugs</i>	<b>CONNECTION</b> 1/8 NPT back <i>Optional, special socket configurations</i>
<b>RANGES</b> 0-60 psi (180° arc); 0-100 psi, 0-160 psi, 0-200 psi, 0-300 psi, 0-400 psi (235° arc) For optimum gauge life, select a gauge with a full scale pressure range of approximately twice the maximum excursion pressure	<b>RANGES</b> 60 psi-100 psi (180° dial arc) 160 psi-300 psi (235° dial arc)  Consult factory for high cycle life applications	<b>RANGES</b> 0/60 psi (180° arc) 0/100 psi, 0/160 psi, 0/200 psi, 0/300 psi, (235° arc) 0/700 psi (200° arc) 0/1,200 psi (180° arc) 0/1,500 psi 0/2,000 psi, 0/3,000 psi, 0/4,000 psi (165° arc)  Consult factory for high cycle life applications	<b>RANGES</b> Maximum scale pressure from 200 psi to 1200 psi
<i>Consult factory for high cycle life applications</i>			* UL 299 UL 626 UL 1058 UL 1093
Typical applications include filter regulator lubricators, portable compressors, air tanks, industrial machinery and a variety of other applications. Excellent shock resistance.	These gauges are perfect for a multitude of applications where a 1 1/2" conventional size gauge is too large, such as mini-FRL's, pneumatic stack valves, air compressors and accessories.	Applications include pumps, air compressors, portable tire inflators, portable oxygen equipment, self-contained breathing apparatus, portable industrial gas cylinders and a variety of other applications.	These products are designed for use on portable fire extinguishers and systems.

## Diaphragm Seals/ Instrument Isolators

### Specification Matrix

Ashcroft Diaphragm Seals &  
Pressure Instrument Isolators

• = AVAILABLE

							
Process Connection Type			Threaded	Threaded w/Flushing Connection	Raised Face Flange	Raised Face Flange w/Flushing Connection	In-line Threaded
Model No.	Code		100/200/300 <sup>(1)</sup>	101/201/301 <sup>(1)</sup>	102/202/302 <sup>(1)</sup>	103/203/303 <sup>(1)</sup>	104/204/304 <sup>(1)</sup>
Process Connection Size (NPT)							
	Female	Male					
1/4	25	02	•	•			•
1/2	50	04	•	•	•	•	•
3/4	75	06	•	•	•	•	•
1	10	08	•	•	•	•	
1 1/2	15				•	•	
2	20				•	•	
3	30				•	•	
4	40						
6	60						
8	80						
Diaphragm Materials							
316L stainless steel	S		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
304L stainless steel	C		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
Monel 400	P		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
Nickel	N		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
Carpenter 20	D		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
Tantalum	U		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
Hastelloy B	G		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
Hastelloy C 22	J		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
Hastelloy C 276	H		100 & 200	101 & 201	102 & 202	103 & 203	104 & 204
Teflon	T		200 & 300	201 & 301	202	203	204 & 304
Viton	Y		200 & 300	201 & 301	202	203	204 & 304
Kalrez	K		200 & 300	201 & 301	302	303	304
Titanium	TI		200	201	202	203	204
Halar Coated Monel	PH		100	101	102	103	104
Bottom Housing Materials							
Steel	B		•	•	•	•	•
304L stainless steel	CL		•	•	•	•	•
316L stainless steel	SL		•	•	•	•	•
Hastelloy B	G		•	•	•	•	•
Hastelloy C 22	J		•	•	•	•	•
Hastelloy C 276	H		•	•	•	•	•
Carpenter 20	D		•	•	•	•	•
Monel 400	M		•	•	•	•	•
Inconel 600	W		•	•	•	•	•
Nickel	N		•	•	•	•	•
PVC	V		(Socket Weld or 1/4-1/2 NPT)		1, 1 1/2		
Tantalum Clad SS	SU				•		
Halar® Coated Monel	SH				•		
Teflon	T				1, 1 1/2, 2		
Kynar	KY		Only 1/4 or 1/2 NPT		1, 1 1/2, 2		
Titanium	TI		•	•	•	•	•
Pressure Ratings							
500 psi			Viton or Kalrez diaph. only	Viton or Kalrez diaph. only			Viton or Kalrez diaph. only
2500 psi			Metal & Teflon® diaph.	•			Metal & Teflon® diaph.
5000 psi	HP		100 & 200 metal				
7500 psi							
15000 psi	HP						
Flange Class							
150, 300, 600, 900 or 1500					Kalrez, Teflon, Viton, Kynar 150 only	Kalrez, Teflon, Viton, Kynar 150 only	
Instrument Connection Size							
1/4	02T		•	•	•	•	•
1/2	04T		•	•	•	•	•
Filling Fluid							
Glycerin	CG		•	•	•	•	•
Silicone (direct to 10" capillary)	CK		•	•	•	•	•
Silicone (over 10" capillary)	EJ		•	•	•	•	•
Halocarbon	CF		•	•	•	•	•
Syltherm	HA		•	•	•	•	•

<sup>(1)</sup> Type 300 series not available with metallic diaphragms

Consult factory for guidance in product selection.  
Phone 203-378-8281, visit our web site  
www.ashcroft.com or email: info@ashcroft.com.

**ASHCROFT®**

## Diaphragm Seals/ Instrument Isolators

### Specification Matrix

Ashcroft Diaphragm Seals &  
Pressure Instrument Isolators

• = AVAILABLE



Process Connection Type			Saddle	In-line Flanged	In-line Socket Weld	In-line Butt Weld	Male/Female Threaded Mini (*Flushing Conn.)
Model No. Code			105/205	106/206	107/207	108	310/315*
Process Connection Size (NPT)	Female	Male					Female Male
1/4	25	02			•	•	• •
1/2	50	04		•	•	•	• •
3/4	75	06		•	•	•	• •
1	10	08		•	•	•	• •
1 1/2	15			•	•	•	• •
2	20			•	•	•	• •
3	30		3"	•			
4	40		4" and larger				
6	60			•			
8	80			•			
Diaphragm Materials							
316L stainless steel	S		•	•	•	•	•
304L stainless steel	C		•	•	•	•	
Monel 400	P		•	•	•	•	•
Nickel	N		•	•	•	•	
Carpenter 20	D		•	•	•	•	
Tantalum	U		•	•	•	•	•
Hastelloy B	G		•	•	•	•	
Hastelloy C 22	J		•	•	•	•	
Hastelloy C 276	H		•	•	•	•	•
Teflon	T		205	206	207	208	
Viton	Y		205	206	207	208	
Kalrez	K		205	206	207	208	
Titanium	TI		205	206	207	208	
Halar Coated Monel	PH		105	106	107	108	
Bottom Housing Materials							
Steel	B		•	•	•	•	
304L stainless steel	CL		•	•	•	•	
316L stainless steel	SL		•	•	•	•	•
Hastelloy B	G		•	•	•	•	
Hastelloy C 22	J		•	•	•	•	
Hastelloy C 276	H		•	•	•	•	•
Carpenter 20	D		•	•	•	•	
Monel 400	M		•	•	•	•	•
Inconel 600	W		•	•	•	•	
Nickel	N		•	•	•	•	
PVC	V						
Tantalum Clad SS	SU						
Halar® Coated Monel	SH						
Teflon	T						
Kynar	KY						
Titanium	TI		•		•	•	
Pressure Ratings							
500 psi			Viton or Kalrez diaph. only		Viton or Kalrez diaph. only	Viton or Kalrez diaph. only	
2500 psi			Metal & Teflon® diaph.		Metal & Teflon® diaph.		
5000 psi	HP						
7500 psi							
15000 psi	HP						
Flange Class							
150, 300, 600, 900 or 1500				150 & 300			
Instrument Connection Size							
1/4	02T		•	•	•	•	•
1/2	04T		•	•	•	•	•
Filling Fluid							
Glycerin	CG		•	•	•	•	•
Silicone (direct to 10" capillary)	CK		•	•	•	•	•
Silicone (over 10" capillary)	EJ		•	•	•	•	•
Halocarbon	CF		•	•	•	•	•
Syltherm	HA		•	•	•	•	•



## Diaphragm Seals/ Instrument Isolators

### Specification Matrix

Ashcroft Diaphragm Seals &  
Pressure Instrument Isolators

• = AVAILABLE








Process Connection Type				Female & Male Threaded		Female Threaded (w/Flushing Conn.)	Quick Connect	1" Male Flush Mini	Threaded (*Flushing Conn.)
Model No.		Code		311		312	320/321	330	400/401*
Process Connection Size (NPT)		Female	Male	Female	Male				
1/4	25	02		•	•	•	•		•
1/2	50	04		•	•	•	•		•
3/4	75	06			•	•			•
1	10	08			•	•		•	•
1 1/2	15						•		
2	20						•		
3	30								
4	40								
6	60								
8	80								
Diaphragm Materials									
316L stainless steel	S			•		•	•	•	•
304L stainless steel	C								
Monel 400	P								•
Nickel	N								
Carpenter 20	D								
Tantalum	U			•		•			•
Hastelloy B	G								•
Hastelloy C 22	J								•
Hastelloy C 276	H			•		•			•
Teflon	T								
Viton	Y								
Kalrez	K								
Titanium	TI								•
Halar Coated Monel	PH								
Bottom Housing Materials									
Steel	B								
304L stainless steel	CL								
316L stainless steel	SL			•		•	•	•	•
Hastelloy B	G								
Hastelloy C 22	J								•
Hastelloy C 276	H			•		•			•
Carpenter 20	D								
Monel 400	M								•
Inconel 600	W								
Nickel	N								
PVC	V								
Tantalum Clad SS	SU								
Halar® Coated Monel	SH								
Teflon	T								
Kynar	KY								
Titanium	TI								
Pressure Ratings									
500 psi									
2500 psi				1000		1000	•		
5000 psi	HP								
7500 psi									4400
15000 psi	HP								9000
Flange Class									
150, 300, 600, 900 or 1500									
Instrument Connection Size									
1/4	02T			•		•	•	•	•
1/2	04T			•		•	2" only	•	•
Filling Fluid									
Glycerin	CG			•		•	•	•	•
Silicone (direct to 10" capillary)	CK			•		•	•	•	•
Silicone (over 10" capillary)	EJ			•		•	•	•	•
Halocarbon	CF			•		•	•	•	•
Syltherm	HA			•		•	•	•	•

## Diaphragm Seals/ Instrument Isolators

### Specification Matrix

Ashcroft Diaphragm Seals &  
Pressure Instrument Isolators

• = AVAILABLE

							
Process Connection Type			Raised Face Flange (*Flushing Conn.)	Threaded (*Flushing Conn.)	Low Pressure Flanged (*w/Flushing Conn.)	Low Pressure Threaded (*w/Flushing Conn.)	Isolation Ring
Model No. Code			402/403*	500/501*	702/703*	740/741*	80/81/85/86
Process Connection Size (NPT)							Pipe Size
Female Male							
1/4						•	1.0" 14.0"
1/2			•	•	•	•	1.5" 16.0"
3/4			•	•	•	•	2.0" 18.0"
1			•	•	•	•	3.0" 20.0"
1 1/2				•			4.0"
2				•			5.0"
3				•			6.0"
4							8.0"
6							10.0"
8							12.0"
Diaphragm Materials							Liner Materials / Code
316L stainless steel			•	•	•	•	Buna N (E)
304L stainless steel							Teflon (T)
Monel 400			•	•	•	•	Viton (Y)
Nickel							Nordell EPDM (EP)
Carpenter 20							White Neoprene (CR)
Tantalum			•	•	•	•	Natural Rubber (NP)
Hastelloy B				•	•	•	
Hastelloy C 22			•	•			
Hastelloy C 276			•	•	•	•	
Teflon							
Viton							
Kalrez							
Titanium				•	•	•	
Halar Coated Monel							
Bottom Housing Materials							Ass'y Flanges / Code
Steel				•		•	Carbon Steel (B)
304L stainless steel							316 SS (S)
316L stainless steel			•	•	•	•	CPVC (CP)
Hastelloy B					•	•	Teflon Enveloped (CT)
Hastelloy C 22			•	•			Polypropylene (PP)
Hastelloy C 276			•	•	•	•	
Carpenter 20					•	•	
Monel 400			•	•	•	•	
Inconel 600							
Nickel							
PVC							
Tantalum Clad SS							
Halar® Coated Monel							
Teflon							
Kynar							
Titanium				•	•	•	
Pressure Ratings							Instrument Conn / Code
500 psi				•	750	750	1/4 NPT (02T)
2500 psi							1/2 NPT (04T)
5000 psi							
7500 psi							
15000 psi							
Flange Class							
150, 300, 600, 900 or 1500			•		150-600		
Instrument Connection Size							
1/4			•	•	•	•	
1/2			•	•	•	•	
Filling Fluid							
Glycerin			•	•	•	•	•
Silicone (direct to 10" capillary)			•	•	•	•	•
Silicone (over 10" capillary)			•	•	•	•	•
Halocarbon			•	•	•	•	•
Syltherm			•	•	•	•	•

## Quick Guide Transducers & Transmitters

### TYPE GC51 RANGEABLE PRESSURE TRANSMITTER



LOOK FOR THIS MARK  
ON OUR PRODUCTS



**REFERENCE CONDITION:** 23°C ±2° (73°F)

**ACCURACY:** ±0.25% FS (URL)  
(Accuracy includes the effects of linearity, hysteresis, and repeatability)  
**Stability:** ±0.25% FS/year  
**Response Time:** 30msec (user adjustable)  
**Output Resolution:** 0.1% FS (URL)  
**Zero Offset:** ≤ ±0.1% FS/year  
**Standard Ranges (Compound):**  
-15 to 15psi, -15 to 30psi, -15 to 50psi  
**Standard Ranges (Gauge):**  
0-50psi, 100psi, 150psi, 300psi, 500psi, 1000psi, 1500psi, 3000psi, 5000psi, 7500psi

**Temperature Limits:**  
**Storage:** -20 to 70°C (-4 to 158°F)  
**Operating:** -10 to 60°C (14 to 140°F)  
**Compensated:** -10 to 60°C (14 to 140°F)  
**Temperature Effects (-10 to 60°C):**  
±0.02% FS (URL)/°C from 23°C reference

Overpressure (F.S.):	Proof	Burst
1500psi and below	200%	500%
3000, 5000psi	150%	300%
7500psi	120%	150%

**Vibration:** 5g's 150Hz  
**Shock:** 10g's 16ms

**Output Signal:** 4-20mA (2 Wire)  
**Supply Voltage:** 12-32Vdc  
**Rangeability / Adjustment<sup>(1)</sup>:**  
Zero -10% to +110% FS  
Span -10% to +110% FS  
<sup>(1)</sup> Accuracy and output resolution based upon full scale (URL) value  
**Insulation Resistance:** 50Vdc (>100Mohms)  
**CE Compliance:** EN 613261 1997, A1/1998, A2/2001 (Heavy Industrial)

**Pressure Connection:** 1/4 Female NPT  
**Enclosure:** Aluminum  
**Rating:** IP65 / NEMA 4X  
**Electrical Connection (Options):**  
- 1/2 Female NPT Conduit  
- Cable Gland (Cable Diameters 0.35" to 0.47")  
**Weight:** Approx. 1.0 lb  
**Mounting:** Mounting Bracket included  
**Media:** Fluids and gases compatible with 316SS and pH17-4 stainless steel

### TYPE GC55 WET/WET DIFFERENTIAL PRESSURE TRANSDUCER



**ACCURACY:** ± 0.5% FS  
(Accuracy includes the effects of linearity, hysteresis and repeatability)  
**Analog Output (4-20mA or 1-5Vdc):**  
**Response Time:** 20msec  
**Output Resolution:** 0.2% FS  
**Stability:** ±0.5%/yr  
**Pressure Switch Output:**  
**Type:** TTL/CMOS up to 40Vdc/200mA  
**Setting Accuracy:** ± 1.0% FS  
**Number of Contacts:** 2  
**Response Time:** 20msec-2.0sec (by user)  
**Hysteresis:** Variable (by user)  
**Display:**  
**Type:** 3 1/2 digits  
**Accuracy:** ± 1.0% FS  
**Standard Ranges (Differential):**  
75psi 250psi  
100psi 300psi  
150psi

**Temperature Limits:**  
**Storage:** -20 to 60°C (-4 to 140°F)  
**Operating:** -10 to 50°C (14 to 122°F)  
**Compensated:** -10 to 50°C (14 to 122°F)  
**Temperature Effects:**  
Zero/Span: ±0.05%FS/°C (from 23°C reference temperature)

Static (Line) Pressure:		
Pressure Range	Proof	Burst
All	2X FS (URL)	10X FS (URL)
Static (Line) Pressure Effects: None		
Single Side (Differential Limits):		
Pressure Range	Proof	Burst
All	2X FS (URL)	10X FS (URL)

Transducer	Supply Voltage	Supply Current
4-20mA (3 wire)	15-27 Vdc	80mA
1-5Vdc (3 wire)	11-27 Vdc	60mA
<b>Switch Contacts:</b> (2) TTL/CMOS relay outputs; Load 200mA (max), 40Vdc; Hysteresis (variable)		
Rangeability / Adjustment <sup>(1)</sup> :		
Zero	-105% to +105% FS	
Span	-105% to +105% FS	
<sup>(1)</sup> Accuracy based upon full scale (URL) value		

**Pressure Connection:** 1/8" Female NPT (2)  
**Enclosure:** Aluminum  
**Rating:** IP64  
**Electrical Connection:**  
**External Options:**  
- 1/2" Female NPT Conduit  
- Cable Gland (Cable Diameters 0.16" to 0.31")  
**Weight:** Approx. 1.0 lb  
**Mounting:** (2) 5.2mm mounting holes (see installation drawings)  
**Media:** Fluids and gases compatible with 304SS (sensor housing) and 17-4 pH SS (sensor diaphragm)

### TYPE X1005, TYPE X2001 XMITR™ TRANSMITTER GAUGE



LOOK FOR THESE AGENCY  
MARKS ON OUR PRODUCTS

**REFERENCE CONDITION:** 20°C (68°F)

**ACCURACY:** Electrical output is 1% BFSL including non-linearity, hysteresis and non-repeatability.  
Gauge is ASME B 40.1 Grade B (±3-2-3% of span)

**TEMPERATURE/ENVIRONMENTAL EFFECTS:**  
**Storage:** -40 to 105°C (-40 to 221°F)  
**Operating:** -40 to 105°C (-40 to 221°F)  
**Compensated:** -20 to 85°C (-4 to 185°F)  
**Thermal effect:** 3%/100°C (1.4%/100°F) typical (zero and fullscale combined)  
**Humidity:** 0 to 95% relative humidity, non-condensing, no effect.  
CE Heavy Industrial

**WETTED MATERIALS:** Bronze/brass or SS

**OUTPUT** 4-20mA, 1-5Vdc,  
.5-4.5Vdc ratio-metric

**INGRESS PROTECTION/ENCLOSURE:**  
Stainless steel case (2", 2.5", 3.5")  
Type X1005, IP54  
Type X2001, IP43 std, IP54 (XLJ)

**FUNCTIONAL SPECIFICATIONS:**  
Type X1005 compound to 600 psi.  
Type X2001 compound to 600 psi.  
**Proof Pressure:**  
0 to 200 psi = 150% full scale  
300 to 600 psi = 120%  
**Burst Pressure:**  
0 to 200 psi = 10x burst  
300 to 600 psi = 3x burst  
**Vibration:** 5g's 50 to 2000 Hz  
**Shock:** 100 g-force per IEC770  
**Response Time:** Less than 10 ms  
CE heavy industrial

2 Instruments in 1. Breakthrough functionality and value. Stainless steel case, 4-20mA and voltage outputs, cable or Hirschmann conn. CE heavy industrial. Per EN61326, Per 1998 ANNEX A

## Transducers & Transmitters

### TYPE X1009 XMITR™ ALL SS TRANSMITTER GAUGE



**REFERENCE CONDITION:** 20°C (68°F)

**ACCURACY:** Electrical output is 1% BFSI including non-linearity, hysteresis and non-repeatability.  
Gauge is ASME B 40.1 Grade 1A (1% of span)

#### TEMPERATURE/ENVIRONMENTAL EFFECTS:

Storage: -40 to 105°C (-40 to 221°F)  
Operating: -40 to 105°C (-40 to 221°F)  
Compensated: -20 to 85°C (-4 to 185°F)  
Thermal effect: 3%/100°C (1.4%/100°F) typical (zero and fullscale combined)  
Humidity: 0 to 95% relative humidity, non-condensing, no effect.  
CE Heavy Industrial

**WETTED MATERIALS:** Bronze/brass or SS

**OUTPUT:** 4-20mA, 1-5Vdc,  
.5-4.5Vdc ratio-metric

**INGRESS PROTECTION/ENCLOSURE:**  
Stainless steel case (2", 2.5", 3.5")  
Type X1009, IP65 (XLJ)

#### FUNCTIONAL SPECIFICATIONS:

Type X1009 compound to 15,000 psi.  
Proof Pressure:  
0 to 600 psi = 125% full scale  
1,000 to 15,000 psi = 110%  
Burst Pressure:  
0 to 1,500 psi = 10x burst  
2,000 to 6,000 psi = 3x burst  
10,000 to 15,000 psi = 3x burst  
Vibration: 5g's 50 to 2000 Hz  
Shock: 100 g-force per IEC770  
Response Time: Less than 10 ms  
CE heavy industrial

2 Instruments in 1. Breakthrough functionality and value. Stainless steel case, 4-20mA and voltage outputs, cable or Hirschmann conn. CE heavy industrial. Per EN61326, Per 1998 ANNEX A

### A2 HEAVY INDUSTRIAL AND EXPLOSION PROOF TRANSMITTERS



**REFERENCE CONDITION:** 21°C (70°F)

**ACCURACY:** Includes non-linearity (Terminal Point Method), hysteresis, non-repeatability, zero offset and span setting errors –  
Three accuracy classes based upon sensor  
Span: ±0.25% ±0.5%, ±1.0%

#### TEMPERATURE/ENVIRONMENTAL EFFECTS:

Storage: -40 to 125°C (-40 to 257°F)  
Operating: -40 to 125°C (-40 to 257°F)  
Compensated: -20 to 85°C (-25 to 185°F)  
Temperature Effects:  
Available 1% to 2% of span over  
-20 to +85°C (-4 to +185°F)  
Humidity: 0 to 100% relative humidity, no effect, with welded enclosure

#### STABILITY:

≤0.1% Span/yr 316L SS construction  
≤0.5% Span/yr 17-4 PH construction

**DURABILITY:** Greater than 10 million cycles

**WETTED MATERIAL(S):** 17-4PH SS  
w/316L SS housing or all 316L SS

**OUTPUT:** 4-20mA, 0-5Vdc, 0-10Vdc,  
1-5Vdc, 1-6Vdc, 0.5-4.5Vdc (ratiometric)

**INGRESS PROTECTION/ENCLOSURE:**  
Available IP65, IP67, NEMA 4X, 6, 7, 9

#### FUNCTIONAL SPECIFICATIONS:

Pressure Ranges (F.S.): 15 to  
7500 psi absolute, 5 to 10,000 psi g,  
compound to 100 psi g  
Overpressure: (Varies w/pressure range)  
Proof: up to 2 x F.S.  
Burst: up to 4 x F.S.  
Vibration: Random 10 g RMS, 20-2000  
Hz; Sweep 50-2000 Hz, 5 g peak  
Shock: 100 g peak, 11 ms  
Drop Test: No effect 1 meter drop on  
concrete  
Response Time: <2ms

#### APPROVALS:

**CE MARK (STANDARD):**  
EN 61326: 1997 +A1: 1998 Annex A  
Heavy Industrial Immunity  
(Annex A, Table A.1)  
Light Industrial/Residential  
Emission (Table 4)

#### EXPLOSION PROOF – UL:

#### EXPLOSION PROOF:

Class I, Div. 1 & 2, Groups A, B, C and D  
Class II, Div. 1 & 2, Groups E, F and G  
**EXPLOSION PROOF – ATEX:**  
CE Ex II 2 GD

Ex d IIC T4

#### INTRINSICALLY SAFE – FM/CSA:

Class I, Div. 1

#### INTRINSICALLY SAFE, NON-INCENDIVE

– FM/CSA:

Class I, Div. 2

A highly configurable transmitter designed for hazardous location and heavy industrial applications. High performance accuracy and thermal capability over -40/125°C (-40/257°F) with additional option of zero and span pots.

### T2 HIGH PERFORMANCE PRESSURE TRANSDUCER



**REFERENCE CONDITION:** 21°C (70°F)

**ACCURACY:** Includes non-linearity, hys-teresis, non-repeatability – BFSI method: ±0.25% of Span

#### TEMPERATURE/ENVIRONMENTAL EFFECTS:

Compensated, Operating, Storage:  
-40 to 125°C (-40 to 257°F)  
Total Error Band combined effects of temperature, non-linearity (Terminal Point Method), hysteresis, non-repeatability, zero offset and span setting errors –  
±1% Span: through -20/85°C (-4/185°F)  
±1.5% Span: through -40/-20°C and (-40/-4°F) and 85/125°C (185/257°F).  
Humidity: 0 to 100% relative humidity, no effect

**STABILITY:** ≤0.25% Span/yr

**DURABILITY:** Tested to 50 million cycles

**WETTED MATERIALS:** 17-4PH SS dia-phragm, 304 SS process connection

**OUTPUT:** 4-20mA, 0-5Vdc, 0-10Vdc,  
1-5Vdc, 1-6Vdc, 0.5-4.5Vdc (ratiometric)

**INGRESS PROTECTION/ENCLOSURE:**  
NEMA 4X, IP65

#### FUNCTIONAL SPECIFICATIONS:

Pressure Ranges (F.S.): 30 to 20,000 psi g,  
compound to 300 psi g  
Overpressure: (Varies w/pressure range)  
Proof: up to 3 x F.S.  
Burst: up to 10 x F.S.  
Vibration: Random (20g) over  
temperature range -40 to 125°C,  
(-40 to 257°F), exceeds typical  
MIL STD requirements  
Shock: 100 g, 6 ms  
Drop Test: No effect 1 meter drop on  
concrete  
Response Time: <1ms  
Approvals: CE compliance per EN 61326:  
1997 +A1:1997 +A2:2001  
Annex A (Heavy Industrial)





A robust pressure transducer designed for industrial applications featuring Ashcroft's proven polysilicon thin film pressure sensing element. Voltage and current outputs, a variety of pressure ports and electrical terminations to international standards with excellent accuracy and performance over -40 to 125°C, (-40 to 257°F)







## Transducers & Transmitters

TYPE G2 OEM PRESSURE TRANSDUCER	KM10 HIGH VOLUME OEM PRESSURE TRANSDUCER	K1/K2 SERIES INDUSTRIAL TRANSDUCER	K8 SERIES TRANSDUCER w/mV SIGNAL																																				
<div><div><div>NEW!</div><div>CE</div><div>LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</div></div></div>	<div><div><div>CE</div><div>LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</div></div></div>	<div><div><div>UL LISTED FM APPROVED</div><div>LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</div></div></div>	<div></div>																																				
REFERENCE CONDITION: 21°C (70°F)	REFERENCE CONDITION: 20°C (68°F)	REFERENCE CONDITION: 20°C (68°F)	REFERENCE CONDITION: 20°C (68°F)																																				
ACCURACY: Total Error Band combined effects of temperature, non-linearity (Terminal Point Method), hysteresis, non-repeatability, zero offset and span setting errors – ±1% Span: through –20/85°C (–4/185°F) ±1.5% Span: through –40/–20°C and (–40/–4°F) and 85/125°C (185/257°F).	ACCURACY: Includes non-linearity (Terminal Point Method), hysteresis, non-repeatability, zero offset and span setting errors – ±0.5% Span, 100 psig F.S. and above ±1.0% Span, 75 psig F.S. and below	ACCURACY: Includes non-linearity (Terminal Point Method), hysteresis, non-repeatability, zero offset and span setting errors – Two accuracy classes based upon sensor Span: ±0.5%, ±1.0%	ACCURACY: Includes non-linearity (Terminal Point Method), hysteresis, non-repeatability, zero offset and span setting errors – Two accuracy classes based upon sensor Span: ±0.5%, ±1.0%																																				
TEMPERATURE/ENVIRONMENTAL EFFECTS: See accuracy, previous, for details Compensated, Operating, Storage: –40 to 125°C (–40 to 257°F) Humidity: 0 to 100% relative humidity, no effect	TEMPERATURE/ENVIRONMENTAL EFFECTS: Storage: –40 to 120°C (–40 to 250°F) Operating: –40 to 120°C (–40 to 250°F) Compensated: –30 to 120°C (–25 to 250°F) Thermal Coefficients: –30 to 120°C (–25 to 250°F) Zero 0.01%/F.S./°C (±0.0055%/F.S./°F) Span 0.01%/F.S./°C (±0.0055%/F.S./°F) Humidity: 0 to 100% relative humidity, no effect	TEMPERATURE/ENVIRONMENTAL EFFECTS: Storage: –54 to 120°C (–65 to 250°F) Operating: –28 to 82°C (–20 to 180°F) Compensated: –28 to 71°C (–20 to 160°F) Thermal Coefficients (20°C/68°F Ref.): <table><tr><td>Accuracy Class (Span)</td><td>Zero/Span (%F.S./°F)</td></tr><tr><td>0.5%</td><td>±0.028</td></tr><tr><td>1.0%</td><td>±0.04</td></tr></table> Humidity: 0 to 95% relative humidity, non-condensing, no effect	Accuracy Class (Span)	Zero/Span (%F.S./°F)	0.5%	±0.028	1.0%	±0.04	TEMPERATURE/ENVIRONMENTAL EFFECTS: Storage: –54 to 120°C (–65 to 250°F) Operating: –28 to 82°C (–20 to 180°F) Compensated: –28 to 82°C (–20 to 180°F) Thermal Coefficients (20°C/68°F Ref.): <table><tr><td>Accuracy Class (Span)</td><td>Zero/Span (%F.S./°F)</td></tr><tr><td>0.5%</td><td>±0.028</td></tr><tr><td>1.0%</td><td>±0.04</td></tr></table> Humidity: 0 to 95% relative humidity, non-condensing, no effect	Accuracy Class (Span)	Zero/Span (%F.S./°F)	0.5%	±0.028	1.0%	±0.04																								
Accuracy Class (Span)	Zero/Span (%F.S./°F)																																						
0.5%	±0.028																																						
1.0%	±0.04																																						
Accuracy Class (Span)	Zero/Span (%F.S./°F)																																						
0.5%	±0.028																																						
1.0%	±0.04																																						
STABILITY: ≤0.25% Span/yr	STABILITY: ±0.25% Span/yr	STABILITY: ±0.50% Span/yr	STABILITY: ±0.50% Span/yr																																				
DURABILITY: Tested to 50 million cycles	DURABILITY: Tested to 50 million cycles	DURABILITY: 100,000,000 cycles	DURABILITY: 100,000,000 cycles																																				
WETTED MATERIALS: 17-4PH SS diaphragm, 304 SS process connection	WETTED MATERIAL(S): 17-4PH SS diaphragm, 304 SS process connection	WETTED MATERIAL(S): 17-4PH SS diaphragm, 316 SS process connection	WETTED MATERIAL(S): 17-4PH SS diaphragm, 316 SS process connection																																				
OUTPUT: 4-20mA, 0-5Vdc, 0-10Vdc, 1-5Vdc, 1-6Vdc, 0.5-4.5Vdc (ratiometric)	OUTPUT: 1-5Vdc, 1-6Vdc, 0.5-4.5Vdc (ratiometric)	OUTPUT: K1: 4-20mA, 1.5Vdc, 1-6Vdc, 1-11Vdc K2: 2, 3, 10, 20 mV/V	OUTPUT: Varies from 6-18 mV/V at F.S. ratiometric																																				
INGRESS PROTECTION/ENCLOSURE: NEMA 4X, IP65 and IP67	INGRESS PROTECTION/ENCLOSURE: IP67	INGRESS PROTECTION/ENCLOSURE: NEMA 1, NEMA 4X	INGRESS PROTECTION/ENCLOSURE: NEMA 4X																																				
FUNCTIONAL SPECIFICATIONS: Pressure Ranges (F.S.): 30 to 20,000 psi g, compound to 300 psi g Overpressure: (Varies w/pressure range) Proof: up to 3 x F.S. Burst: up to 10 x F.S. Vibration: Random (20g) over temperature range –40 to 125°C, (–40 to 257°F), exceeds typical MIL STD requirements Shock: 100 g, 6 ms Drop Test: No effect 1 meter drop on concrete Response Time: <1ms Approvals: CE compliance per EN 61326: 1997 +A1:1997 +A2:2001 Annex A (Heavy Industrial)	FUNCTIONAL SPECIFICATIONS: Pressure Ranges (F.S.): 15 to 7500 psi g/s, compound to 300 psi g Overpressure (F.S.): <table><tr><td></td><td>Proof</td><td>Burst</td></tr><tr><td>≤ 3000 psig</td><td>2 x F.S.</td><td>5 x F.S.</td></tr><tr><td>5000 psig</td><td>1.5 x F.S.</td><td>5 x F.S.</td></tr><tr><td>7500 tpsig</td><td>1.2 x F.S.</td><td>5 x F.S.</td></tr></table> Vibration: Random to 1 KHz Shock: 50 g, 11 ms Drop Test: No effect 1 meter drop on concrete Response Time: <1ms Approvals: CE compliance per EN 61326: 1997 Annex A 1998(A1) Warm-up Time: <25 ms		Proof	Burst	≤ 3000 psig	2 x F.S.	5 x F.S.	5000 psig	1.5 x F.S.	5 x F.S.	7500 tpsig	1.2 x F.S.	5 x F.S.	FUNCTIONAL SPECIFICATIONS: Pressure Ranges (F.S.): 15 to 20,000 psi g, compound to 60 psi g Overpressure (F.S.): <table><tr><td></td><td>Proof</td><td>Burst</td></tr><tr><td>≤ 2000 psig</td><td>2 x F.S.</td><td>8 x F.S.</td></tr><tr><td>3000 to 5000 psig</td><td>1.5 x F.S.</td><td>3 x F.S.</td></tr><tr><td>7500 to 20,000 psig</td><td>1.2 x F.S.</td><td>1.5 x F.S.</td></tr></table> Vibration: 0-2000 Hz at 20 g in any axis Shock: 100 g, 20 ms Response Time: <5ms		Proof	Burst	≤ 2000 psig	2 x F.S.	8 x F.S.	3000 to 5000 psig	1.5 x F.S.	3 x F.S.	7500 to 20,000 psig	1.2 x F.S.	1.5 x F.S.	FUNCTIONAL SPECIFICATIONS: Pressure Ranges (F.S.): 45 to 20,000 psi g Overpressure (F.S.): <table><tr><td></td><td>Proof</td><td>Burst</td></tr><tr><td>≤ 2000 psig</td><td>2 x F.S.</td><td>2 x F.S.</td></tr><tr><td>3000 to 5000 psig</td><td>1.5 x F.S.</td><td>3 x F.S.</td></tr><tr><td>7500 to 20,000 psig</td><td>1.2 x F.S.</td><td>1.5 x F.S.</td></tr></table> Vibration: 0-2000 Hz at 20 g in any axis Shock: 100 g, 20 ms shock in any direction		Proof	Burst	≤ 2000 psig	2 x F.S.	2 x F.S.	3000 to 5000 psig	1.5 x F.S.	3 x F.S.	7500 to 20,000 psig	1.2 x F.S.	1.5 x F.S.
	Proof	Burst																																					
≤ 3000 psig	2 x F.S.	5 x F.S.																																					
5000 psig	1.5 x F.S.	5 x F.S.																																					
7500 tpsig	1.2 x F.S.	5 x F.S.																																					
	Proof	Burst																																					
≤ 2000 psig	2 x F.S.	8 x F.S.																																					
3000 to 5000 psig	1.5 x F.S.	3 x F.S.																																					
7500 to 20,000 psig	1.2 x F.S.	1.5 x F.S.																																					
	Proof	Burst																																					
≤ 2000 psig	2 x F.S.	2 x F.S.																																					
3000 to 5000 psig	1.5 x F.S.	3 x F.S.																																					
7500 to 20,000 psig	1.2 x F.S.	1.5 x F.S.																																					
An economical transducer designed for the high volume OEM. Excellent accuracy and performance over –40/125°C temperature range. IP67 ingress rating and 100V/m EMC immunity.	An economical transducer designed for the high volume OEM. Voltage outputs, a variety of pressure ports and electrical terminations to international standards with excellent accuracy and performance over –30 to 120°C (–25 to 250°F). IP67 ingress rating and 100V/m EMC immunity.	A versatile and proven industrial transducer with an extensive installed base. Wide range of pressure fittings and electrical terminations along with FM & UL hazardous area approvals.	A pressure transducer for applications that can incorporate an unconditioned mV/V output and require the proven benefits of the polysilicon thin film pressure sensing element. A broad range of pressure fittings allow the user design flexibility in packaging.																																				

## Transducers & Transmitters

KX/KS SERIES SANITARY TRANSDUCERS	TYPE GC52 RANGEABLE WET/WET DIFFERENTIAL PRESSURE TRANSMITTER	DIN/PANEL/WALL MOUNT CXLdp SERIES	DIN MOUNT DXLdp SERIES
 <p>KX KS</p>	 <p>CE LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</p>	 <p>NEW! CE LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</p>	 <p>CE LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</p>
<p><b>REFERENCE CONDITION:</b> 20°C (68°F)</p> <p><b>ACCURACY:</b> Includes non-linearity (Terminal Point Method), hysteresis, non-repeatability, zero offset and span setting errors – ±1.0% Span</p> <p><b>TEMPERATURE/ENVIRONMENTAL EFFECTS:</b></p> <p>Storage: –54 to 120°C (–65 to 250°F) Operating: –28 to 82°C (–20 to 180°F) Compensated:</p> <p>KS –0 to 50°C (–30 to 130°F) KX –28 to 71°C (–20 to 160°F)</p> <p>Thermal Coefficients (20°C/68°F Ref.), (%F.S./°F): Zero ±0.04 Span ±0.04</p> <p>Humidity: 0 to 95% relative humidity, non-condensing, no effect</p> <p><b>STABILITY:</b> ±0.50% Span/yr</p> <p><b>WETTED MATERIAL(S):</b> KS: 316L SS diaphragm and process connection KX: 316Ti SS diaphragm and 316 SS process connection</p> <p><b>FILL FLUIDS:</b> KS: USP grade 99.5% glycerine fill KX: Silicone</p> <p><b>OUTPUT:</b> KS: 4-20mA, 1.5Vdc, 1-6Vdc; 2, 3, 10, 20 mV/V ratiometric KX: 4-20mA, 1.5Vdc, 1-6Vdc</p> <p><b>INGRESS PROTECTION/ENCLOSURE:</b> NEMA 4X</p> <p><b>FUNCTIONAL SPECIFICATIONS:</b> Pressure Ranges (F.S.): KS: 30 to 1000 psi g, compound to 100 psig Kx: 100 to 5000 psi gi g Overpressure (F.S.): ≤ 2000 psig 2 x F.S. 8 x F.S. 3000 to 5000 psig 1.5 x F.S. 3 x F.S. Vibration: 0-400 Hz at 20 g in any axis Shock: 20 g, 20 ms in any axis</p>	<p><b>REFERENCE CONDITION:</b> 23°C ±2° (73°F)</p> <p><b>Accuracy:</b> ±0.50% FS (URL) (Accuracy includes the effects of linearity, hysteresis, and repeatability) <b>Stability:</b> ±0.25% FS/year <b>Response Time:</b> 100msec (adjustable) <b>Output Resolution:</b> 0.1% FS (URL) <b>Standard Ranges (Bi-Directional, Inches W.C.):</b> ±4, ±8, ±20, ±40, ±80, ±200 <b>Standard Ranges (Uni-Directional, Inches W.C.):</b> 0-4, 8, 20, 40, 80, 200, 400</p> <p><b>Temperature Limits:</b> Storage: –15 to 65°C (5 to 150°F) Operating: –10 to 60°C (14 to 140°F) Compensated: –10 to 60°C (14 to 140°F) <b>Temperature Effects (–10 to 60°C):</b> ±0.03% FS/°C (from reference, 23°C (73°F))</p> <p><b>Static (Line) Pressure:</b> Pressure Range      Proof      Burst All                      300 psi      1000 psi</p> <p><b>Static (Line) Pressure Effects:</b> Pressure Range      Effect ≥ 20" W.C., ±8" W.C.      ±0.3% FS/100psi 8" W.C., ±4" W.C.      ±0.7% FS/100psi 4" W.C.      ±1.5% FS/100psi</p> <p><b>Single Side (Differential) Limits:</b> Pressure Range      Proof      Burst ≤ 8" W.C., ±4" W.C.      30 psid      130 psid ≥ 20" W.C., ±8" W.C.      100 psid      130 psid Vibration: 5g's 150Hz Shock: 10g's 16ms</p> <p><b>Output Signal:</b> 4-20mA (2 Wire) <b>Supply Voltage:</b> 12-32Vdc <b>Rangeability / Adjustment<sup>(1)</sup>:</b> Zero –10% to +110% FS Span –10% to +110% FS <sup>(1)</sup> Accuracy and output resolution based upon full scale (URL) value <b>Insulation Resistance:</b> 50Vdc (&gt;100Mohms) <b>CE Compliance:</b> EN 613261 1997, A1/1998, A2/2001 (Heavy Industrial)</p> <p><b>Pressure Connection:</b> 1/4 Female NPT <b>Enclosure:</b> Aluminum <b>Rating:</b> IP65 / NEMA 4X <b>Electrical Connection (Options):</b> – 1/2 Female NPT Conduit – Cable Gland (Cable Diameters 0.35" to 0.47") <b>Weight:</b> Approx. 1.0 lb <b>Mounting:</b> Mounting Bracket included <b>Media:</b> Fluids and gases compatible with 316SS, Viton and Alumina</p>	<p><b>PRESSURE RANGES (Inches W.C.)</b> Unidirectional: 0/0.10 to 0/25 I.W.C. Bidirectional: ±0.10 to ±15 I.W.C.</p> <p><b>ACCURACY:</b> 0.8% or 0.4% span</p> <p><b>TEMPERATURE LIMITS</b> Storage: –40 to 180°F Operating: 0 to 160°F Compensated: –35 to 130°F</p> <p><b>OVERPRESSURE</b> Proof Pressure: 15 psi Burst Pressure: 25 psi</p> <p><b>OUTPUT SIGNAL</b> 4-20mA, (12-36Vdc), 0-5, 0/10Vdc (24Vac)</p> <p><b>ENCLOSURE</b> NEMA 1</p> <p><b>MATERIALS</b> ABS (UL94-5V4)</p> <p><b>PRESSURE CONNECTIONS</b> 1/4 Brass Barb 1/2 NPT Female</p> <p><b>MEDIA</b> Clean, dry and non-corrosive gas</p> <p><b>MOUNTING</b> DIN rail or panel mount</p> <p>NOT FOR USE ON LIQUIDS</p>	<p><b>PRESSURE RANGES (Inches W.C.)</b> Unidirectional: 0/0.10 to 0/50 I.W.C. Bidirectional: ±0.05 to ±25 I.W.C.</p> <p><b>ACCURACY:</b> 0.25% or 0.50% span Non-lin (Term.Pt.) ±0.20 ±0.40 (B.S.F.L.) ±0.15 ±0.30 Hysteresis ±0.02 ±0.02 Non-Repeatability ±0.03 ±0.05</p> <p><b>TEMPERATURE LIMITS</b> Storage: –40 to 180°F Operating: –20 to 160°F Compensated: –35 to 135°F</p> <p><b>OVERPRESSURE</b> Proof Pressure: 15 psi Burst Pressure: 25 psi Max. static (line) pressure: 25 psi</p> <p><b>OUTPUT SIGNAL</b> 4-20mA, 1-5Vdc, 1-6Vdc, 0-5, 0/10Vdc</p> <p><b>ENCLOSURE</b> NEMA 1</p> <p><b>MATERIALS</b> Glass-filled Polycarbonate (UL94-V-1)</p> <p><b>PRESSURE CONNECTIONS</b> 1/2 NPTF Brass</p> <p><b>MEDIA</b> Clean, dry and non-corrosive gas (consult factory for use on other media)</p> <p><b>MOUNTING</b> DIN rail mount: EN50022 EN50035 EN50045</p> <p>NOT FOR USE ON LIQUIDS</p>
<p>For use in sanitary, waste-water, food processing and pharmaceutical applications. The KS Series features a 316L stainless steel electropolished TriClamp style diaphragm while the KX Series features several options designed for harsh applications – flush mounted diaphragm, PMC adapter or weldnuts. The polysilicon thin film pressure sensing element offers proven performance and stability.</p>		<p>Static or velocity pressure measurement for flow stations, ducts, building pressure, filter efficiency, van boxes or room pressurization.</p>	<p>Designed for ease of installation and system calibration, the DXLdp is ideal for pharmaceutical plants and other installations where large numbers of air flow and dp measurements are being monitored.</p>

## Transducers & Transmitters

REDUCED SIZE RXLdp SERIES	HIGH PERFORMANCE XLdp SERIES	INDUSTRIAL IXLdp SERIES	2279 DURATRAN® PRESSURE TRANSMITTER
 <p><b>3 YEAR WARRANTY</b></p> <p>CE LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</p>	 <p><b>3 YEAR WARRANTY</b></p> <p>CE LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</p>	 <p><b>3 YEAR WARRANTY</b></p> <p>FM APPROVED LOOK FOR THESE AGENCY MARKS ON OUR PRODUCTS</p>	 <p><b>PLUS! Performance</b></p>
<b>PRESSURE RANGES (Inches W.C.)</b> Unidirectional: 0/0.10 to 0/50 I.W.C. Bidirectional: ±0.05 to ±25 I.W.C.	<b>PRESSURE RANGES (Inches W.C.)</b> Unidirectional: 0/0.10 to 0/50 I.W.C. Bidirectional: ±0.05 to ±25 I.W.C.	<b>PRESSURE RANGES (Inches W.C.)</b> Unidirectional: 0/0.10 to 0/200 I.W.C. Bidirectional: ±0.05 to ±100 I.W.C.	<b>ACCURACY</b> ±0.5%
<b>ACCURACY CLASS F.S.</b> <b>1%</b> Non-lin (Term.Pt.)    ±0.80 (B.S.F.L.)    ±0.60 Hysteresis    ±0.05 Non-Repeatability    ±0.10	<b>ACCURACY CLASS F.S.</b> <b>0.25% 0.50%</b> Non-lin (Term.Pt.)    ±0.20 ±0.40 (B.S.F.L.)    ±0.15 ±0.30 Hysteresis    ±0.02 ±0.02 Non-Repeatability    ±0.03 ±0.05	<b>ACCURACY CLASS F.S.</b> <b>0.25% 0.50%</b> Non-lin (Term.Pt.)    ±0.20 ±0.40 (B.S.F.L.)    ±0.15 ±0.30 Hysteresis    ±0.02 ±0.02 Non-Repeatability    ±0.03 ±0.05	<b>DIAL SIZE</b> 4 1/2" analog  <b>CASE MATERIAL</b> Phenolic
<b>TEMPERATURE LIMITS</b> Storage:    -40 to 180°F Operating:    0 to 160°F Compensated:    +40 to 125°F	<b>TEMPERATURE LIMITS</b> Storage:    -40 to 180°F Operating:    -20 to 160°F Compensated:    +35 to 135°F	<b>TEMPERATURE LIMITS</b> Storage:    -40 to 210°F Operating:    -20 to 185°F Compensated:    0 to 160°F	<b>WETTED MATERIAL</b> 316 stainless steel, Monel  <b>SENSING ELEMENT</b> Bourdon tube
<b>OVERPRESSURE</b> Proof Pressure:    15 psi Burst Pressure:    25 psi Max. static (line) pressure:    25 psi	<b>OVERPRESSURE</b> Proof Pressure:    15 psi Burst Pressure:    25 psi Max. static (line) pressure:    25 psi	<b>OVERPRESSURE</b> Proof Pressure:    20 psi Burst Pressure:    50 psi Maxi. static (line) pressure:    100 psi	<b>CONNECTION – NPT</b> 1/2 NPT (standard) lower
<b>OUTPUT SIGNAL</b> 4-20mA, 1-5Vdc, 1-6Vdc, 0-5, 0/10Vdc	<b>OUTPUT SIGNAL</b> 4-20mA, 1-5Vdc, 1-6Vdc	<b>APPROVALS (optional)</b> FM-IS & Nonincendive	<b>RANGES</b> Vacuum and compound, 12 to 20,000 psi
<b>ENCLOSURE</b> NEMA 1	<b>ENCLOSURE</b> NEMA 2	<b>OUTPUT SIGNAL</b> 4-20mA, 1-5Vdc, 1-6Vdc, ±5Vdc, ±2.5Vdc	<b>ENCLOSURE</b> NEMA 4X
<b>MATERIALS</b> Case is Stainless Steel Cover is Polycarbonate	<b>MATERIAL</b> 300 Series Stainless Steel	<b>ENCLOSURE</b> NEMA 4X	<b>MATERIAL</b> 300 Series Cast Stainless Steel
<b>PROCESS CONNECTIONS</b> 1/4" Barbed Stainless Steel 1/8" Barbed Stainless Steel 1/8 NPTF Stainless Steel	<b>PROCESS CONNECTIONS</b> 1/4" Barbed Stainless Steel 1/8" Barbed Stainless Steel 1/4 NPTF Stainless Steel	<b>PROCESS CONNECTIONS</b> 1/4 NPTF St. St.	<b>PROCESS CONNECTIONS</b> 1/4 NPTF St. St.
<b>MEDIA</b> Clean, dry and non-corrosive gas (consult factory for use on other media)	<b>MEDIA</b> Clean, dry and non-corrosive gas (consult factory for use on other media)	<b>MEDIA</b> Clean, dry and non-corrosive gas (consult factory for use on other media)	<b>MEDIA</b> Clean, dry and non-corrosive gas (consult factory for use on other media)
NOT FOR USE ON LIQUIDS	NOT FOR USE ON LIQUIDS	NOT FOR USE ON LIQUIDS	NOT FOR USE ON LIQUIDS
A compact transmitter for comfort control and other HVAC applications.	High performance dp transmitter with proven reliability and stability. Excellent for air handling applications including fume hood control and room pressurization.	A rugged low pressure transmitter in cast 300 series stainless steel enclosure. A good choice for dp monitoring in pollution control, combustion control, and other applications where precision sensing is needed in a tough environment.	Two instruments in one! Provides local indication and 4-20mA signal for many industrial applications.

EDISON



## Temperature Instruments

FT POCKET TEST COMMERCIAL THERMOMETERS	EI, CI & EL INDUSTRIAL BIMETAL THERMOMETERS	600A & 600B DURATEMP® THERMOMETERS	2400E & 2410E DIGITAL THERMOMETERS
			
<b>ACCURACY</b> ASME B 40.3 Grade A ( $\pm 1\%$ of span)	<b>ACCURACY</b> ASME B 40.3 Grade A ( $\pm 1\%$ of span)	<b>ACCURACY</b> ASME B 40.3 Grade A ( $\pm 1\%$ of span)	<b>RESOLUTION</b> 1°
<b>DIAL SIZE</b> 1"	<b>DIAL SIZE</b> EI, CI 2", 3", 5" (EL 3", 5")	<b>DIAL SIZE</b> 600A – 4 1/2", 6" 600B – 4 1/2"	<b>UPDATE TIME</b> 3 readings per second
<b>STEM/BULB DESIGN</b> Rigid stem 0.142" dia.	<b>STEM/BULB DESIGN</b> Rigid stem 0.250" dia.	<b>STEM/BULB DESIGN</b> Rigid stem 0.375" dia. (600B) Bendable 0.375" dia. (600A)	<b>CASE SIZE</b> 2.030" dia. x 1.39"
<b>RECALIBRATOR</b> External	<b>RECALIBRATOR</b> (EI, EL external), (CI none)	<b>RECALIBRATOR</b> Adjustable pointer	<b>CASE</b> ABS and acrylic
<b>SEALING DESIGN</b> Hermetically sealed	<b>SEALING DESIGN</b> Hermetically sealed; EL liquid filled	<b>RECALIBRATOR</b> Weatherproof	<b>VIBRATION</b> 50 to 200 Hz @ 2.5g no effect
<b>DAMPENING</b> Silicone-dampened bimetal coil	<b>DAMPENING</b> Silicone-dampened bimetal coil; EL liquid filled	<b>DAMPENING</b> Silicone-encapsulated helical Bourdon tube	<b>RANGE</b> –40°F to 199°F; 0°F to 250°F, –40°C to 120°C
<b>CONNECTION LOCATION</b> Rear	<b>CONNECTION LOCATION</b> EI rear, lower, Everyangle™ mount CI rear, lower EL rear, Everyangle mount	<b>CONNECTION LOCATION</b> 600A – rear, lower – remote mount 600B – Everyangle – direct mount	<b>AMBIENT TEMP. LIMIT</b> –30°F to 160°F (–34°C to 71°C)
<b>CONNECTION SIZES (NPT)</b> Plain	<b>CONNECTION SIZES (NPT)</b> Plain 1/4 (2" sizes only) 1/2 and 1/2 union (3", 5" sizes only)	<b>CONNECTION SIZES (NPT)</b> 1/2" union	<b>ZERO &amp; SPAN</b> $\pm 10\%$ of operating range through two single-turn potentiometers located on the back of the thermometer's module
<b>STEM LENGTH</b> 5"	<b>CONNECTION SIZES (NPT)</b> Plain 1/4 (2" sizes only) 1/2 and 1/2 union (3", 5" sizes only)	<b>STEM LENGTH</b> 6"–36" – 600B	<b>POWER</b> 110 Vac input – 6 Vdc regulated output (220 Vac or 24 Vac optional)
<b>RANGES</b> –80°F to 550°F –30°C to 300°C	<b>STEM LENGTH</b> 2 1/2"–60"	<b>CAPILLARY LENGTH</b> 5'–80' – 600A	<b>HUMIDITY LIMITS</b> Up to 100% RH @ 140°F max.
<b>CASE/RING MATERIAL</b> Stainless steel (no ring)	<b>RANGES</b> –80°F to 1000°F, –50°C to 500°C EL –40°F to 550°F, –20°C to 300°C	<b>RANGES</b> –320°F to 1200°F –200°C to 650°C	<b>APPROVALS</b> UL recognized (File: E103515), NSF C-2, CSA (File: Natl/C, LR 76285-2)
<b>CASE/BULB MATERIAL</b> Stainless steel	<b>CASE/RING MATERIAL</b> Stainless steel	<b>CASE/RING MATERIAL</b> Stainless steel, aluminum, phenol	<b>SENSOR</b> Laser trimmed 2000 ohm RTD 0.250" dia. x 2.54" long 300 series stainless steel with 8' wire cable
<b>WINDOW</b> Polycarbonate	<b>CASE/BULB MATERIAL</b> Stainless steel	<b>CASE/BULB MATERIAL</b> Stainless steel	<b>WEIGHT</b> Display – 35g (0.08lb) Power Supply – 211g (0.5lb)
	<b>WINDOW</b> EI, CI glass (EL Polycarbonate)	<b>CAPILLARY MATERIAL</b> 600A– 300 Series stainless steel	
		<b>WINDOW</b> Glass	
Applications include sample testing of food vats, cooking or air duct temperature use. Compact and portable.	General industrial temperature applications including gases, liquids, and other proc-esses. All stainless steel construction.	Rugged applications including gases, liquids and other processes. Wide temperature ranges including remote monitoring.	Applications include freezers, coolers and food storage equipment where remote monitoring and solid state digital readout is preferred.

EDISON

## Pressure and Temperature Switches

SINGLE SETPOINT WATERTIGHT ENCLOSURES	SINGLE SETPOINT EXPLOSION PROOF ENCLOSURES	DUAL SETPOINT WATERTIGHT ENCLOSURES	DUAL SETPOINT EXPLOSION PROOF ENCLOSURES
<p style="text-align: center;"><b>B-SERIES</b></p> 	<p style="text-align: center;"><b>B-SERIES</b></p> 	<p style="text-align: center;"><b>L-SERIES</b></p> 	<p style="text-align: center;"><b>P-SERIES</b></p> 
<p><b>FEATURES</b></p> <p><b>Enclosure:</b> Watertight epoxy-coated aluminum NEMA 4, 4X, IP66</p> <p><b>Switch Function:</b> Single setpoint, fixed deadband, SPDT (or) Single setpoint, fixed deadband, (2) SPDT (DPDT action)</p> <p><b>Wetted Materials:</b> Stainless steel and Buna, *Teflon® or Viton® (or) All-welded stainless steel (or) All-welded Monel</p> <p><b>Ranges:</b> Pressure: vac. thru 3000 psi Temperature: -40°F thru 750°F Differential Pressure: 30 in.H<sub>2</sub>O diff. thru 600 psid H-Series Pressure: 1000 – 7500 psi</p>	<p><b>FEATURES</b></p> <p><b>Enclosure:</b> Explosion proof, NEMA 7/9, IP66</p> <p><b>Switch Function:</b> Single setpoint, fixed deadband, SPDT (or) Single setpoint, fixed deadband, (2) SPDT (DPDT action)</p> <p><b>Wetted Materials:</b> Stainless steel, Buna, Teflon® or Viton® (or) All-welded stainless steel (or) All-welded Monel</p> <p><b>Ranges:</b> Pressure: vac. thru 3000 psi Temperature: -40°F thru 750°F Differential Pressure: 30 in.H<sub>2</sub>O diff. thru 600 psid</p> <p>U.L. or CSA LISTED, ATEX and IECEx models for Hazardous locations now available.</p>	<p><b>FEATURES</b></p> <p><b>Enclosure:</b> Watertight epoxy-coated aluminum NEMA 4, 4X, IP66</p> <p><b>Switch Function:</b> Single setpoint, fixed deadband, SPDT contacts (or) Single setpoint, fixed deadband, (2) SPDT contacts (DPDT action) (or) Single setpoint, adjustable deadband, SPDT contacts (or) Dual setpoint, fixed deadband, (2) SPDT contacts, (DPDT action)</p> <p><b>Wetted Materials:</b> Stainless steel and Buna, Teflon® or Viton® (or) All-welded stainless steel (or) All-welded Monel</p> <p><b>Ranges:</b> Pressure: vac. thru 3000 psi Temperature: -40°F thru 750°F Differential Pressure: 30 in.H<sub>2</sub>O diff. thru 400 psid</p>	<p><b>FEATURES</b></p> <p><b>Enclosure:</b> Watertight epoxy-coated aluminum explosion-proof NEMA 7/9, IP66</p> <p><b>Switch Function:</b> Single setpoint, fixed deadband, SPDT contacts (or) Single setpoint, fixed deadband (2) SPDT contacts (DPDT action) (or) Single setpoint, adjustable deadband, SPDT contacts (or) Dual setpoint, fixed deadband (2) SPDT contacts, (DPDT action)</p> <p><b>Wetted Materials:</b> Stainless steel and Buna, Teflon® or Viton® (or) All-welded stainless steel (or) All-welded Monel</p> <p><b>Ranges:</b> Pressure: vac. thru 3000 psi Temperature: -40°F thru 750°F Differential Pressure: 30 in.H<sub>2</sub>O diff. thru 400 psid</p>
<p>U.L. and CSA LISTED</p> <p>*Registered trademark of E. I. DuPont</p> <div style="display: flex; justify-content: space-around; align-items: center;">   </div> <p>LOOK FOR THIS AGENCY MARK ON OUR PRODUCTS</p>	<div style="display: flex; justify-content: space-around; align-items: center;">   </div> <p>LOOK FOR THIS AGENCY MARK ON OUR PRODUCTS</p>	<p>U.L. and CSA LISTED</p> <div style="display: flex; justify-content: space-around; align-items: center;">   </div> <p>LOOK FOR THIS AGENCY MARK ON OUR PRODUCTS</p>	<p>U.L. or CSA LISTED</p> <div style="display: flex; justify-content: space-around; align-items: center;">   </div> <p>LOOK FOR THIS AGENCY MARK ON OUR PRODUCTS</p>
<p>General purpose switches for most industrial and process applications. Models are available for steam and fuel pressure-limit controls on boilers and burners. Ideal for compressors, turbines, filters, blowers, etc.</p>	<p>Ashcroft 700 series has been developed for most applications found in process plants U.L. or CSA LISTED.</p> <p>All models have similar performance characteristics to the popular Ashcroft B400 Series switch line, which has been used throughout the world's plants and mills for over 25 years. They feature rugged, reliable diaphragm-sealed piston actuators, snap-acting contacts and all-popular wetted materials and process connections. Optional hermetically sealed contacts, Monel or fire-safe actuators and scores of options allow you to choose a model for any application.</p>	<p>Easy-to-use L-Series switches are specifically suited for the OEM seeking more features in a snap-acting switch. Single or dual setpoints and fixed or adjustable deadband models with many wetted materials and electrical ratings are offered. This snap-acting switch also replaces older mercury models and is cost effective.</p> <p>L-Series switches are ideal for blowers, generators, scrubbers, precipitators, compressors and turbines.</p>	<p>More varieties and more features are available in the highly reliable P-Series switch which is especially suited for process and refinery applications. Dual chamber design allows setpoint changes to be made safely, even with power connected. Features include NEMA 4X/ NEMA 7/9 enclosure, with single or dual setpoints, fixed or adjustable deadbands, with many wetted materials and electrical ratings. Optional, all-welded stainless steel or Monel actuators are ideal for applications requiring NACE or fire-safe conformance. Optional UL listed, hermetically sealed switch contacts improve safety and reliability.</p>

## Pressure and Temperature Switches

WATERTIGHT STAINLESS STEEL ENCLOSURES	COMPACT EXPLOSION PROOF PRESSURE	MINIATURE PRESSURE SWITCHES	ELECTRONIC PRESSURE SWITCHES.
<p><b>G-SERIES</b></p> 	<p><b>F-SERIES</b></p> 	<p><b>A-SERIES</b></p> 	<p><b>N-SERIES</b></p> 
<p><b>FEATURES</b></p> <p><b>Enclosure:</b> Watertight 316 stainless steel NEMA 4, 4X, IP65</p> <p><b>Switch Function:</b> Single setpoint, fixed deadband, SPDT contacts (or) Single setpoint, fixed deadband (2) SPDT contacts (DPDT action) (or) Single setpoint, adjustable deadband, SPDT contacts (or) Dual setpoint, fixed deadband (2) SPDT contacts (DPDT action)</p> <p><b>Wetted Materials:</b> Stainless steel and Buna, Teflon® or Viton® (or) All-welded stainless steel (or) All-welded Monel</p> <p><b>Ranges:</b> Pressure: vac. thru 3000 psi Temperature: -40°F thru 750°F Differential Pressure: 30 in.H<sub>2</sub>O diff. thru 400 psid</p>	<p><b>FEATURES</b></p> <p><b>Enclosure (Body):</b> Explosion-proof, anodized aluminum NEMA 7/9, IP66</p> <p><b>Switch Function:</b> Single setpoint, field-adjustable fixed deadband, SPDT contacts (or) Single setpoint, field-adjustable fixed deadband, (2) SPDT contacts (DPDT action)</p> <p><b>Wetted Materials:</b> 316 stainless steel pressure connection and choice of: Buna N, Teflon® or Viton® diaphragm and O-ring (or) All-welded 316 stainless steel diaphragm</p> <p><b>Ranges:</b> Pressure: vac. thru 4000 psi</p>	<p><b>FEATURES</b></p> <p><b>Enclosure:</b> NEMA 4X watertight or NEMA 7/9 explosion proof, IP66</p> <p><b>Switch Function:</b> Single setpoint, fixed deadband, factory set SPDT contacts (or) Single setpoint, fixed deadband, field-adjustable SPDT contacts</p> <p><b>Wetted Material:</b> Brass (Buna N, Viton® or Teflon® actuator) Stainless steel</p> <p><b>Ranges:</b> Vac thru 2000 psi.</p>	<p><b>FEATURES</b></p> <p><b>Enclosure:</b> NEMA 4X watertight or NEMA 7/9 explosion proof, IP66</p> <p><b>Switch Function:</b> Single setpoint with adjustable deadband</p> <p><b>Wetted Material:</b> Stainless steel</p> <p><b>Ranges:</b> 60 thru 20,000 psi. Deadbands as low as 0.1% of range.</p> <p><b>Optional process and setpoint indication and 4-20mA transmitter output available.</b></p>
<p>U.L. and CSA LISTED</p>   <p>The stainless steel enclosure offers greater corrosion protection for this high-performance switch in breweries, dairies, chemical and petrochemical plants, offshore rigs and pulp and paper mills. Our standard diaphragm-sealed piston actuators and a variety of wetted materials are available in these pressure, temperature and differential pressure switches.</p>	<p>U.L. and CSA LISTED</p>   <p>Compact size facilitates mounting in panels and other installations where space is a premium.</p> <p>Standard hermetically sealed switch element and sealed conduit connection eliminate the possibility of condensation entering the enclosure from the conduit. Standard 1/2 NPTF pressure connection makes retrofit on existing installations quick and easy.</p>	<p>U.L. and CSA LISTED</p>  <p>You should consider Ashcroft A-Series pressure switches for use on heavy vehicles, engines and compressors, electronics processing and medical equipment, food and beverage processing equipment, garbage compactors, machine tools, or any equipment where space is a consideration. This series is especially suitable for OEM configuration.</p>	 <p>The Ashcroft N-Series electronic pressure switch combines the popular K-Series polysilicon thin film pressure transducer sensor and rugged, epoxy-coated enclosures. The result is a highly reliable pressure switch that is ideal for high cycle, high pressure, or difficult deadband applications.</p> <p>Typical applications include: machine tools, injection molding machines, presses, pumps, hydraulic systems, turbines, and compressors.</p>



## Pressure and Temperature Switches

### STANDARD DIFFERENTIAL PRESSURE SWITCH



Small size and high overpressure capability make our differential pressure switch ideal for most process and industrial applications. Minimum static working pressures of 500 psi allow use on the most difficult filter applications.

We use a unique combination of diaphragm-sealed piston actuators to get our high static pressure performance in 12 ranges.

For inches of water ranges, we use a large diaphragm for sensitivity which results in lower, more conventional working pressure. Consult the factory for application assistance on differential pressure switch selection.

### ATEX APPROVAL FOR HAZARDOUS LOCATIONS



LOOK FOR THIS AGENCY MARK ON OUR PRODUCTS

ATEX is a European designation that deals with standards for equipment and protective systems intended for use in potentially explosive atmospheres. This approval is required for switches intended for use in hazardous locations, especially important to OEMs who export to Europe and contractors specifying or purchasing products for European applications.

XCN option adds special features to Ashcroft 700-Series switch enclosures that meet the requirements for the highest levels of security and danger, such as:

- Special locking device requiring an Allen wrench to remove cover
- Special vents that blow out should the diaphragm rupture, thus preventing pressure build-up in the enclosure
- Special conduit plug requiring an Allen wrench for removal
- Available on pressure, temperature and d/p models
- Meets explosion class EEx d IIC T6

### U.L. LISTED STEAM LIMIT CONTROL



The Ashcroft steam-limit control switch is designed for use on boilers equipped with electrically operated burners. The limit control is an adjustable pressure-operated switch set to stop burner operation when the recommended safe boiler working pressure is exceeded.

We recommend a stainless steel diaphragm for steam service. A pigtail siphon should also be used to reduce the possibility of high temperature affecting switch performance. This listing is available for setpoints up to 300 psi.

### U.L. LISTED PRESSURE LIMIT CONTROL



The Ashcroft medium-pressure gas and oil limit control switch is designed for use with air, LP gas, natural gas, #1 and #2 fuel oil and #6 oil preheated to 240°F. This limit control is an adjustable pressure-operated switch with a secondary chamber to prevent fuel from entering the switch enclosure in the unlikely event that the diaphragm develops a leak. The control shuts down a fuel pump in high or low pressure conditions.

EDISON

EDISON

#### **World Headquarters**

Ashcroft Inc.  
250 East Main Street  
Stratford, CT 06614-5145  
U.S.A.  
Tel: (203) 378-8281  
Fax: (203) 385-0408  
email: [info@ashcroft.com](mailto:info@ashcroft.com)  
[www.ashcroft.com](http://www.ashcroft.com)

#### **International Operations**

##### **Brazil**

Willy Instrumentos de Medicao  
e Controle Ltda.  
Rua Americo Brasiliense, 90  
09529-030 Sao Caetano Do Sul  
Sao Paulo, Brazil  
Tel: 55-11-4224-7400  
Fax: 55-11-4224-7477  
email:  
[vendas.instrumentos@ashcroft.com](mailto:vendas.instrumentos@ashcroft.com)

##### **China**

Ashcroft China Representative Office  
Room 203, First Shanghai Center,  
No. 39 Liang Ma Qiao Road  
Beijing, China 100016  
Tel: 86-10-8453-5127  
86-10-8453-5259  
Fax: 86-10-8453-5259  
email: [sales@ashcroft.com.cn](mailto:sales@ashcroft.com.cn)

##### **China**

Ashcroft Instruments (Suzhou) Co., Ltd  
Blk 3 Phase 1A  
Ascendas Lin-hu Industrial Square  
1508 Lin-hu Avenue  
Wujiang Fenu Economic Zone  
Wujiang, China 215211  
Tel: 86-512-6326-9101  
Fax: 86-512-6326-9106

##### **France**

Ashcroft GmbH Sales Office  
206, Rue des Campanules,  
Le Mandinet, 77185 Lognes  
France  
Tel: 33 (0) 1 60 37 25 30  
Fax: 33 (0) 1 60 37 25 39  
[www.ashcroft.europe@wanadoo.com](mailto:www.ashcroft.europe@wanadoo.com)

##### **Germany**

Ashcroft GmbH  
Postfach 11 20  
Max-Planck-Strasse 1  
D-52499 Baesweiler, Germany  
Tel: 49-2401-8080  
Fax: 49-2401-7027

##### **India**

Ashcroft India  
Shed-N Shriram Ind. Co. Op. Soc. Ltd.  
Ram Mandir Road  
Goregaon (W), Mumbai, India 400 104  
Fax: [alpesh.patel@ashcroftindia.com](mailto:alpesh.patel@ashcroftindia.com)

##### **Mexico**

Ashcroft Instruments México, S.A. de C.V.  
Mariano Arista No. 54 Nave 8, Bodega 8  
Col. Argentina Poniente  
Deleg. Miguel Hidalgo  
11230 Mexico City, Mexico  
Tel: 525-55-082-3030 - Main  
525-55-082-3060  
525-55-082-5053  
525-55-527-5360  
525-55-527-4434  
Fax: 525-55-082-3027  
email: [jmendieta@ashcroft.com.mx](mailto:jmendieta@ashcroft.com.mx)

##### **Saudi Arabia**

AARICO  
P.O. Box 10145  
Jubail Industrial City  
Saudi Arabia 31961  
Kingdom of Saudi Arabia  
Tel: 966-3-341-0278  
Fax: 966-3-341-7624

##### **Singapore**

Ashcroft Instruments Singapore Pte. Ltd.  
Block 1004 Toa Payoh North  
#07-15/17  
Singapore 318995  
Tel: 65-252-6602  
Fax: 65-252-6603  
email: [sales@ashcroft.com.sg](mailto:sales@ashcroft.com.sg)

##### **United Kingdom**

Ashcroft GmbH Sales Office  
Cambridge Office  
Unit 5 William James House  
Cowley Road  
Cambridge CB4 0WX  
Tel: 44-0-1223-395500  
Fax: 44-0-1223-395501  
email: [sales@ashcrofteurope.net](mailto:sales@ashcrofteurope.net)

##### **Venezuela**

Manufacturas Petroleras Venezolanas S.A.  
KM7 Carretera A  
El Mojan Calle 18  
#15B355 Zona  
Ind. Norte Sector Canchancha  
Maracaibo Edo Zulia Venezuela  
Tel: 58-261-757-9070  
Tel: 58-261-742-4372  
Fax: 58-261-757-9461  
email: [contactenos@mapvensa.com](mailto:contactenos@mapvensa.com)  
[www.mapvensa.com](http://www.mapvensa.com)

**Visit our web site at [www.ashcroft.com](http://www.ashcroft.com)**