

Model HPO Precision Analog Pressure Transducers



Shown with optional Bendix PTO connection

FEATURES

- **Accuracy $\pm 0.05\%$ F.S. or better**
- **Absolute, gauge, vacuum or compound pressure types**
- **High-level voltage or current output**
- **Superior long-term stability and repeatability**
- **NEMA 4X housing**
- **Isolated 4-wire voltage output available**
- **Externally accessible zero and span adjustments**
- **Broad pressure media compatibility**
- **Accuracy is expressed as the sum of nonlinearity, nonrepeatability and hysteresis at reference conditions of 72°F**
- **Improved shock resistance**
- **Gettered absolute sensors**

The Heise® HPO precision pressure transducers combine the time-proven precision and stability of the Heise photo-optic sensor with an all-new SMD electronics circuit. These features provide exceptional performance with accuracies of $\pm 0.05\%$ of span or better. The patented photo-optic sensor has no moving parts, linkages, epoxies or O-rings which can contribute to drift and instability.

The wetted materials are 300 series stainless steel and Inconel X718. The welded construction of the pressure sensor boundary ensures long life and broad pressure-media compatibility. Standard pressure fittings include $\frac{1}{4}$ male NPT and $\frac{1}{16}$ -18 UNF-2B For $\frac{1}{4}$ " O.D. high pressure tubing. For barometric and absolute ranges up to 30 psia, exceptional long-term stability is ensured by the inclusion of a getter material in the evacuated reference chamber. This material acts like a sponge to absorb gas molecules as they are released from the surface of the reference chamber. This ensures the integrity of the vacuum reference over time.

PRODUCT SPECIFICATIONS

Accuracy: Within $\pm 0.05\%$ of span including nonlinearity, hysteresis, and nonrepeatability at reference conditions (72°F)

Temperature Effects:

Storage: -40 to 200°F
 Operating: -40 to 150°F
 Compensated Range: 20 to 120°F
 Temperature coefficients:
 $\pm 0.004\%$ F.S. per °F from 72°F
 Thermal Repeatability:
 $\pm 0.025\%$ F.S. (typical)

Response Time: 3ms (typical)

Frequency Response: 300 Hz

Warm-up Time: 5 minutes to rated accuracy, 30 minutes to full stability

Shock: 1000G in 3 mutually perpendicular axes – no effect on calibration

Service: Gas, vapor or liquid

Pressure Ranges*: 0-5 psi through 0-10,000 psi or equivalent metric ranges *See Price Sheet HPO/PS for complete range listings

Pressure Types: Gauge, absolute, vacuum, and compound

Overpressure Limit:

4 times span 0/5 to 0/250 psi
 1.3 times span 0/300 to 0/10,000 psi

Sensor Volume:

Approximately 4 cc to 250 psi
 Approximately 0.38 cc above 250 psi

Volumetric Displacement:

Approximately 0.5 cc to 250 psi
 Negligible for ranges over 250 psi

Mounting Position Effect: Less than the values indicated below per 30 degree inclination in any plane for zero only – no effect on span

Up to 250 psi: 0.05% of span (max)
 Over 250 psi: 0.3% of span (max)

Note: Correctable by zero adjustment

Output Signals: 0/5 Vdc, 0/10 Vdc, -5/+5 Vdc (3 wire or optional 4 wire), or 4/20 mA (2 wire)

Resolution: 0.01% FSO

Power Requirements:

20-40 Vdc (voltage output)
 12-40 Vdc (current output)

Power Supply Effect:

Negligible over operating range

Zero Adjustment:

Externally accessible $\pm 3\%$ F.S. (typical)

Span Adjustment:

Externally accessible $\pm 3\%$ F.S. (typical)

Wetted Materials: Inconel 718 and 300 Series Stainless Steel

Process Connection:

$\frac{1}{4}$ male NPT through 5000 psi.
 $\frac{1}{16}$ -18 UNF-2B high pressure over 5000 psi

Electrical Connector:

3-foot pigtail – standard
 Bendix PTO – optional


Housing: 304 stainless steel, sealed (NEMA 4X) with vent through pigtail connector

Mounting: Stem, optional pipe/wall mounting bracket

Weight: 10 oz

Model HPO Precision Analog Pressure Transducers

Dimensions



Loop Resistance

