

Flexible conduits polyester



3871 56

3872 56

CP braid

Polyester extendable braid. High abrasion and bending resistance. Very low absorption of moisture. The given diameters are approximate.

Characteristics:

material: Polyester fibre
temperature rating: -50°C +150°C
temperature MAX: 175°C
flame resistance: UL 224
fluids resistance: very high to oils, solvents and hydrocarbons

halogen free

pack (m)	cat. nos. grey	diameter conduits	rta cat. nos.
200	3871 50	2-5	CP3
200	3871 51	4-8	CP5
200	3871 52	6-12	CP8
100	3871 53	7-15	CP10
100	3871 54	10-18	CP12
50	3871 55	12-23	CP15
50	3871 56	16-28	CP20
50	3871 57	21-35	CP25
50	3871 58	26-45	CP30
50	3871 59	36-60	CP40
50	3871 60	45-75	CP50

pack (m)	cat. nos. black	diameter conduits	rta cat. nos.
200	3872 50	2-5	CP3N
200	3872 51	4-8	CP5N
200	3872 52	6-12	CP8N
100	3872 53	7-15	CP10N
100	3872 54	10-18	CP12N
50	3872 55	12-23	CP15N
50	3872 56	16-28	CP20N
50	3872 57	21-35	CP25N
50	3872 58	26-45	CP30N
50	3872 59	36-60	CP40N
50	3872 60	45-75	CP50N

Flexible conduit cutting tools



3814 45



3814 46



3814 47

Cutting vice

Metal tool equipped with an adjustable clamp and a perpendicular guide for a hacksaw blade. Suitable for cutting plastic and metal flexible conduits up to 40 mm inside diameter.

pack	cat. nos.	rta cat. nos.
1	3814 45	5445

Cutting vice

Hand shears

Ideal cutting tool for PVC and PA6 conduits. Provides a neat, square cut for conduits without metal core up to 18 mm outside diameter.

pack	cat. nos.	rta cat. nos.
1	3814 46	5446

Hand shears

pack	cat. nos.	rta cat. nos.
1	3814 42	5442

Spare blade

Bench shears

Screws to the bench, suitable for low volume production. Provides a neat, square cut for conduits without metal core up to 60 mm outside diameter.

pack	cat. nos.	rta cat. nos.
1	3814 47	5447

Bench shears

pack	cat. nos.	rta cat. nos.
1	3814 43	5443

Spare blade

Accessories for metal fittings

2000 connectors

Table of Adaptor rings for 2000 connectors

Øi conduit	GE-PVC	FP 2000	FA2000 FA	PN	P2 P2 AT/BT P2X	LA	FTR	GNS GND GNDX	GDAX TRS
10	AR	AR	 AG10	AR	AR		AR	 AX10	 AT10
12	AR	AR	 AG12	AR	AR	AR	AR	 AX12	 AT12
15 – 16	AR	AR	 AN16	AR	AR	AR	AR	 AX16	 AT16
20 - 21	AR	AR	 AN21	AR	AR	AR	AR	 AX21	 AT21
27	AR	AR	 AN27	AR	AR	AR	AR	 AX27	 AT27
35 – 36	AR	AR	 AN35	AR	AR	AR	AR	 AX35	 AT35
40	AR	AR	 AN40	AR	AR	AR	AR	 AX40	 AT40
51 – 52	AR	AR	 AN52	AR	AR	AR	 AB52	 AX52	 AT52
63					AR	AR			 AT63
77					AR	AR			
102					AR	AR			

NOTE: 2000 connectors are supplied with red AR lock ring. To allow coupling to different ranges of conduit, specific adaptor rings are available to separate order.